
## High Quality Power Cord UL Certificated

## multicomp



Plug Component				
Colour	Component	Qty		
35P (Black)	ME-301 (Nema 5-15P)	1		
Nickel-plated	4.75 GEM 98475ABS-1 (#14-#18) (Earth Pins Terminal)	1		
Nickel-plated	6.3×15 (#14AWG) GEM 98675BBS-1 (Solid Blades)	2		
Black	301-1 (5-15P Inner Body)	1		

## Note:

- 1. Hi-Pot Test : 1,500V/1Sec; <0.5mA
- 2. Insulation Resistance Test : DC 500/min>100m $\Omega$
- 3. Continuity & Polarization Test : No short circuit, break circuit, displacement.
- 4. Each end terminal shall be capable of withstanding a pull of 25lbs for 1 minutes without loosening.
- 5. Strain relief shall be capable of withstanding a pull of 35lbs for 1 minutes with out loosening.
- 6. All material according to Non-toxic standard.

Dimension					
Strip	ROJ	Colour			
6 +1/-0	22 ±2	Black (L)			
6 +1/-0	22 ±2	White (N)			
6 +1/-0	22 ±2	Green (E)			

Wire Styles SJ 14AWGx3C 90°C Black Length : 4572mm ±50.8mm

180.6	±Ζ	

Dimensions				
ROJ	Strip	Colour		
51±6	19 ±3	Black (L)		
51±6	19 ±3	White (N)		
51±6	19 ±3	Green (E)		

Dimensions : Millimetres

## Part Number Table

Description	Part Number
5-15P, SJ, 14/3C, Rubber, 15A 125V	MC-160

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com

