50Ω Coaxial Cable **RG58C/U, 20AWG**





RoHS **Compliant**

Description

20AWG Stranded TACW, Solid PE Insulation, TACW Braiding 95% Coverage, PVC Sheath.

Application

For CATV/MATV, Broadband, HDTV and Satellite Broadcasting Transmission use.

Construction

Conductor

Material : Tinned Annealed Copper Wire

Size : 20AWG

Construction : Stranded (19/0.19mm)

Insulation

Material : Solid PE Nominal O.D : 2.95mm

Braiding

Material : TACW, 95% Coverage

Sheath

Material : PVC Nominal O.D : 5.0mm Colour : Black

Physical Properties

Min. Bend Radius : 50mm

: -15°C to 60°C **Operating Temperature**

Electrical Properties

Rated Voltage : 30V Max. Conductor DC Resistance @20°C : 35.4Ω/km Nom. Characteristic Impedance : $50\pm3\Omega$ (10MHz) Nom. Capacitance : 107±2pF/m (1kHz)

Nom. Velocity of Propagation : 66%

: 2,300V AC/1min Voltage test: Core to Shielding

Max. Attenuation (dB/100m)

(MHz)	1	10	50	100	200	400	700	900	1000
(dB)	1.4	4.6	10.8	16.1	23.9	37.7	55.8	65.6	70.5







50Ω Coaxial Cable RG58C/U, 20AWG

pro-**Power**

Diagram





Part Number Table

Description	Part Number		
50Ω Coaxial Cable RG58C/U 20AWG, PVC Sheath	CBBR0441		

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

