
Audio Converter Series

500W Symmetric Boost Converter For Car Audio (PS-SP12148)



Key Features:

- ·A mature DC/DC Boost Converter
- ·LED status indicator
- ·Voltage adjustable via DIP switch
- ·Independent heatsink
- ·Smart fan for heat dissipation
- Input line with a fuse protection
- ·Weight: 405g/0.89 lbs (±10%)
- ·Size: 4.8"X3.6"

Electrical Specifications


Specifications typical @ +25 ℃, Powered by 12V DC, unless otherwise noted. Specifications subject to change without notice.

Parameter	Conditions	Min.	Тур.	Max.	Units
Power Supply	-	11	12	27	VDC
EN enabled Voltage	-	-	12	-	V
Output Power	-	-	500	-	W
Oscillation Frequency	-	-	55	-	KHz
Quiescent Current	VIN=12V	-	20	-	mA
Operating Temperature	-	0	20	80	$^{\circ}\mathbb{C}$
Storage Temperature	-	-20	20	105	$^{\circ}\mathbb{C}$
Thermal Shutdown Temperature	-	-	150	-	$^{\circ}\mathbb{C}$

Note

Stresses beyond the listed maximum power supply voltage may cause the permanent damage to components on board.

Model Selection Guide





Environmental Conditions:

·Humidity: 5-85% RH Noncondensing


Operating Temperature Ambient: 0°C to +55°C

·Storage Temperature: -40 °C to 85 °C

All these boards are per-tested with our power supply solution. For all customers who need those information, please contact our distributor or Sure Electronics. RoHS compliant will need an MOQ of 1000pcs per order.

FC ((RoHS

Mechanical Dimensions




Dimension	A (inch/ mm)	A1 (inch/ mm)	B (inch/ mm)	B1 (inch/ mm)	D (inch/ mm)
#1	4.8/ 121.92	4.4/ 111.76	3.6/ 91.44	3.2/ 81.28	0.2/5.08

Notes:

- · All dimensions are typical in inches (mm)
- Tolerance x.xx = $\pm 0.02 (\pm 0.50)$

Connections



Power Supply Connector: J1.J2 Terminal Block RJ128

Pin	Function	
3,4	GND	
5,6	VIN	

EN Connector:

· J3 Terminal Block RJ128

Pin	Function	
1	EN	
2	12V	

Standby: EN connected to 12V(Short circuit)

Output Connector

J4 Terminal Block RJ128

Pin	Function	
1	OUT+	
2	OUT-	



Sure Electronics Have Fun With Us!