
## USB 2.0 Cable Assembly USB Micro USB A Plug To USB Type A Receptacle multicomp



### **Specifications**

- Waterproof Rate IP67 Rating Max. for Panel Thickness No. of Contacts
- : IP67
- : Immersed in 1M water for 30 minutes
- : 30V 1A
- : 2.5mm
- : 4

Diagram



#### **Dimensions : Millimetres**


#### **Specifications Table**

| Item | Description      | Material                          | Plating and Colour |
|------|------------------|-----------------------------------|--------------------|
| Α    | PCB              | FR-4                              | Green              |
| В    | O-Ring           | EPDM                              | Black              |
| С    | Sealing Nut      | PPE                               |                    |
| D    | Gasket           | EPDM                              |                    |
| F    | Screw Nut        | PPE                               |                    |
| G    | Housing          |                                   |                    |
| Н    | USB A Jack       | P/N:2UB1518-000111                | White Plastic      |
| Ι    | Cable            | 28AWG × 1P+24 AWG × 2C+AL+D+B(UV) | Black (PVC Jacket) |
| J    | Over Mold        | PVC                               | Black              |
| K    | USB Plug         | Micro USB A 5P Plug               | Black Plastic      |
| L    | Waterproof Cap   | P/N:2UB3001-W0000W                | N/A                |
| М    | Inner Mold       | LD-PE                             | White              |
| Ν    | Heat Shrink Tube | Ø1.0 125°C 300V L:10              | Black              |

www.element14.com www.farnell.com www.newark.com



# USB A Plug To USB Type A Receptacle Multicomp



| Shield  | Drain         | Shield  |
|---------|---------------|---------|
| Conn. 2 | Wire Colour   | Conn. 1 |
| 1       | Red (24AWG)   | 1       |
| 2       | White (28AWG) | 2       |
| 3       | Green (28AWG) | 3       |
| 4+5     | Black (24AWG) | 4       |

**Pin Assignments Front View** 

#### Part Number Table

| Description  | Part Number    |
|--|----------------|
| USB Cable, USB Type A Receptacle,<br>Micro USB Type A Plug, 500mm, 19.7", USB 2.0, Black | 2UB3001-W05102 |

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com www.farnell.com www.newark.com

