

SSQ-115-04-S-T



SOCKET STRIP SSW & SSQ SERIES

SPECIFICATIONS

For complete specifications see www.samtec.com?SSW or www.samtec.com?SSQ

Insulator Material:

Black Liquid Crystal Polymer (-S & -D) or Black High Temperature Thermoplastic (-T)

Contact Material:

Phosphor Bronze

Plating:

Au or Sn over 50µ" (1.27µm) Ni

Operating Temp Range:

-55°C to +125°C with Gold
-55°C to +105°C with Tin

Contact Resistance:

10 mΩ max

Insertion Depth:

(3.68mm) .145" to (6.35mm) .250"

Insertion Force:

(Single contact only) (-S plating)

Standard= 6oz (1.67N) avg

((0.64mm) .025" SQ pin);

SSW Low Insertion Force=

3oz (0.83N) avg

SSQ Low Insertion Force=

3.3oz (0.92N) avg

Normal Force:

Standard= 125grams (4.4N)

Withdrawal Force:

(Single contact only) (-S plating)

Standard= 5oz (1.39N) avg

((0.64mm) .025" SQ pin);

SSW Low Insertion Force=

2.6oz (0.72N) avg

SSQ Low Insertion Force=

2.9oz (0.81N) avg

Max Cycles:

100 with 10µ" (0.25µm) Au

Voltage Rating:

550 VAC mated with TSW

RoHS Compliant:

Yes

CURRENT RATING	
AMBIENT TEMPERATURE	SSW mated with TSW
20°C	5.5A
40°C	5A
60°C	4A
80°C	3A

Processing:

Lead-Free Solderable:

Yes


Note:

Some lengths, styles and options are non-standard, non-returnable.

Mates With:
TSW, MTSW, MTLW,
LCW, EW, ZW, TSS,
ZSS, TSM, TSSH




TYPE STRIP	PIN CENTERS	NO. PINS PER ROW
SSW = Solder Tail	-1 = (2,54mm) .100" Centers	
SSQ = Square Tail		



01 thru 50

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM



SSW-115-02-T-Q-RA

SSQ-130-02-S-S

SSW-122-03-S-T

SSW-130-02-G-D-RA

LEAD STYLE

PLATING OPTION

ROW OPTION

TAIL OPTION

OTHER OPTION

-F

= Gold flash on contact, Matte Tin on tail

-G

= 20 μ " (0,51 μ m) Gold on contact, Gold flash on tail

-T

= Matte Tin (-T N/A on LIF contacts)

-S

= 30 μ " (0,76 μ m) Gold on contact, Matte Tin on tail

-S

= Single Row

-P

= Single Row (Notched to mate with LCW) 36 pins max

-D

= Double Row

-T

= Triple Row

-Q


= Double Row .200" (5,08mm) row space (Outer rows filled only)

-RA

= Right Angle (Leave blank for straight pin version)

-LL

= Locking Lead



Two leads per strip crimped in opposite directions on or near centerline. Available on tails from (2,29) .090" to (7,87) .310" only. N/A with single row 1 or 2 positions.

-“XXX”


= Polarized (Specify “XXX” as position number)

Straight Pin Versions (Specify “LEAD STYLE” from chart)

LEAD STYLE		SINGLE DOUBLE OR TRIPLE A
Standard Insertion Force	Low Insertion Force*	
-01	-21	(2,64) .104
-02	-22	(4,93) .194
-03	-23	(10,00) .394
-04	-24	(14,83) .584
-06**	N/A	(3,00) .118

* LIF N/A with Tin Plating


**Style -06 N/A with SSQ



Right Angle Versions (Specify “LEAD STYLE” from chart)

LEAD STYLE		SINGLE	DOUBLE	TRIPLE
Standard Insertion Force	Low Insertion Force*	(-S & -P) A	(-D) A	(-T & -Q) A
-02	-22	(2,54) .100	(2,54) .100	(2,54) .100
-03	-23	(7,62) .300	(7,62) .300	N/A
-04	-24	(12,45) .490	N/A	N/A

*LIF N/A with Tin Plating



Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM