Aug.1.2016 Copyright 2016 HIROSE ELECTRIC CO., LTD. All Rights Reserved.

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					. .
△					. .
△					. .

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					. .
△					. .
△					. .







NOTE 1. LEAD CO-PLANARITY SHALL BE 0.1mm MAX.
2. FOR MODIFICATION,ETC.,PREVENTIVE HOLE FOR SINK MARK MAY BE ADDED ACCORDING TO CIRCUMSTANCES.
3. THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

RECOMMENDED LAND PATTERN DIMENSION OF PCB (MOUNTING SIDE) (2:1)



NO.	MATERIAL	FINISH, REMARKS
1	PPS	LIGHT BROWN (UL94V-0)
2	PHOSPHOR BRONZE	CONTACT AREA:GOLD 0.1μm min. LEAD AREA:GOLD FLASH UNDER PLATING:NICKEL 0.5μm min.

CODE NO.(OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	K.NAKAMURA 05.11.15	K.NAKAMURA 05.11.15	Y.Ogawa '05.11.16	H.Okawa '05.11.16	

SCALE	UNITS	DRAWING NO.	PART NO.	CODE NO.	
5 : 1	mm	EDC3-150825-25	FX8C-140P-SV(71)	CL578-0507-5-71	1/1

HRS HIROSE ELECTRIC CO.,LTD.

TO
PCK

HRS DRAWING FOR REFERENCE

FORM NO.229