



NOTES 1 CONTACT AREA:GOLD PLATING 0.2 μ m min.
 TERMINAL AREA:GOLD FLASH.
 UNDER PLATING:NICKEL 2 μ m min.
 2 CHECK THAT THE O-RING IS PROPERLY SET AT THE GROOVE OF THE DEVICE.
 WHILE MOUNTING THE CONNECTOR,MAKE SURE THAT THE O-RING IS NOT CAUGHT.

2	POLYPHENYLENE SULFIDE (BLACK) UL94V-0						
1	ZINC ALLOY	BLACK CHROMATE TREATMENT (Cr3)	3	COPPER ALLOY			
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS		
UNITS		SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm		2 : 1					
HRS HIROSE ELECTRIC CO., LTD.		APPROVED : MO. SATOH	07. 04. 05	DRAWING NO.	EDC3-114744-00		
		CHECED : MO. SATOH	07. 04. 05	PART NO.	HR34B-12WRA-10P		
		DESIGNED : DS. MATSUNE	07. 04. 05	CODE NO.	CL134-0016-6-00		
		DRAWN : MK. SATO	07. 03. 30				