Feb.1.2017 Copyright 2017 HIROSE ELECTRIC CO., LTD. All Rights Reserved.

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					. .	△					. .
△					. .	△					. .
△					. .	△					. .



RECOMMENDED PC BOARD HOLE PATTERN









PART No.	HRS No.	PIN	A	B	C	D	POLARIZING KEY MOUNT
HIF3FC- 10PA-2.54DSA(71)	CL616-0161-4-71	10	20.2	17.5	10.16	4.1	NONE
HIF3FC- 14PA-2.54DSA(71)	CL616-0162-7-71	14	25.28	22.58	15.24	4.1	1 ON RH SIDE
HIF3FC- 16PA-2.54DSA(71)	CL616-0163-0-71	16	27.82	25.12	17.78	4.1	
HIF3FC- 20PA-2.54DSA(71)	CL616-0164-2-71	20	32.9	30.2	22.86	4.1	
HIF3FC- 26PA-2.54DSA(71)	CL616-0165-5-71	26	40.52	37.82	30.48	4.1	
HIF3FC- 30PA-2.54DSA(71)	CL616-0166-8-71	30	45.6	42.9	35.56	4.1	1 EACH ON LH & RH SIDE.
HIF3FC- 34PA-2.54DSA(71)	CL616-0167-0-71	34	50.68	47.98	40.64	4.1	
HIF3FC- 40PA-2.54DSA(71)	CL616-0168-3-71	40	58.3	55.6	48.26	4.1	
HIF3FC- 50PA-2.54DSA(71)	CL616-0169-6-71	50	71.0	68.3	60.96	4.1	
HIF3FCA-50PA-2.54DSA(71)	CL616-0170-5-71	50	71.0	68.3	60.96	26.96	

NOTE 1 "HIF3FC-10PA-2.54DSA(71)" HAS NO STAND-OFF.
2 THE NUMBER OF POLARIZING KEY MOUNT DIFFERS AS TO THE NUMBER OF PIN, REFER TO THE TABLE.
3 ** INDICATES THE NUMBER OF PIN.
4 THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
1	POLYBUTYLENE TEREPHTHALATE	BLACK, UL94 V-0	4	BRASS	CONTACT AREA:GOLD 0.2μm min. MOUNTING AREA:TIN 2μm min. UNDER PLATING:NICKEL 2μm min.

CODE NO.(OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	T.NODA '05.04.05	K.Doi '05.04.06	H.Ogawa '05.04.06	H.Okawa 05.04.06	

SCALE	DRAWING NO.	PART NO.
FREE	EDC3-151845-21	HIF3FC-**PA-2.54DSA(71)
UNITS: mm	HIROSE ELECTRIC CO., LTD	CODE NO. CL616 — 1/1

TO
PCK

HRS DRAWING FOR REFERENCE