

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0

Revision Date: 16.12.2010 Superseded date: 02.03.2010

# DOW CORNING(R) 732 MULTI-PURPOSE SEALANT CLEAR

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

1.1 Product name : DOW CORNING(R) 732 MULTI-PURPOSE SEALANT CLEAR

1.2 Identified uses : Adhesive, binding agents

Uses advised against : None known.

1.3 Company : Dow Corning Europe S.A.

rue Jules Bordet - Parc Industriel - Zone C

B-7180 Seneffe Belgium

E-mail address (Safety

Data Sheet)

sdseu@dowcorning.com

Customer Service : English

 English
 Tel: +49 611237507

 Deutsch
 Tel: +49 611237500

 Français
 Tel: +32 64511149

 Italiano
 Tel: +32 64511170

 Español
 Tel: +32 64511163

Fax: +32 64888683

1.4 Emergency Phone

Number

Dow Corning (Barry U.K. 24h)

Dow Corning (Wiesbaden 24h) Dow Corning (Seneffe 24h) Tel: +44 1446732350 Tel: +49 61122158 Tel: +32 64 888240

#### 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

According to EU Directives 67/548/EEC or 1999/45/EC:

Not hazardous.

2.2 Label elements

Labelling according to EEC Directive

S-phrases : S24/25 Avoid contact with skin and eyes.

S51 Use only in well-ventilated areas.



According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0

Revision Date: 16.12.2010 Superseded date: 02.03.2010

# DOW CORNING(R) 732 MULTI-PURPOSE SEALANT CLEAR

3.	COMPOSITION /	INFORMATION (	NC	INGREDIENTS
-	COTITE COTTENTI	AL IA CARLIALA A A CALL		ALTERACE AND LAND

Chemical characterization: Silicone elastomer

According to EU Directives 67/548/EEC or 1999/45/EC:

Name	CAS-No.	EINECS/ ELINCS No.	REACH Registration Number	Conc. (% w/w)	Classification	
Triacetoxy(ethyl)silane	17689-77-9	241-677-4	er-sentad partie	2.2		R14
					C	R34
					Xn	R22
Methyltriacetoxysilane	4253-34-3	224-221-9	- mag com	2.1		R14
					C	R34
					Xn	R22

#### According to Regulation (EC) No. 1272/2008:

Name	CAS-No.	EINECS/ ELINCS	REACH Registration	Conc. (% w/w)	Classification
Triacetoxy(ethyl)silane	17689-77-9	No. 241-677-4	Number -	2.2	Acute toxicity (Oral): Category 4 - H302 Skin corrosion/irritation: Category 1B - H314 EUH014
Methyltriacetoxysilane	4253-34-3	224-221-9	Wiesbaden 24h) iemeilo 24b) = -	2.1	Acute toxicity (Oral): Category 4 - H302 Skin corrosion/irritation: Category 1C - H314 EUH014

For the full text of the R-phrases mentioned in this Section, see Section 16. For the full text of the H-Statements mentioned in this Section, see Section 16.

CLP classifications are based on all current available data including from known international organizations. These classifications are subject to revision as more information becomes available.

## 4. FIRST AID MEASURES

## 4.1 Description of First Aid Measures:

On contact with eyes

: Flush with water.

On skin contact

: Flush with water. Wipe off. If skin irritation persists, get medical attention.

If inhaled

: Remove to fresh air.

On ingestion

: No first aid should be needed.



According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0

Revision Date: 16.12.2010

Superseded date: 02.03.2010

## DOW CORNING(R) 732 MULTI-PURPOSE SEALANT CLEAR

## 5. FIRE-FIGHTING MEASURES

5.1 Suitable extinguishing media

On large fires use dry chemical, foam or water spray (fog). On small fires use carbon dioxide (CO2), dry chemical or water spray. Water can be used to cool fire exposed containers.

Unsuitable extinguishing

None known.

media

5.2 Hazards during fire fighting

: None known.

**Hazardous Combustion** 

**Products** 

: Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.

5.3 Special protective equipment/procedures

A self-contained respirator and protective clothing should be worn. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to

keep fire exposed containers cool.

#### 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear proper protective equipment.

6.2 Environmental precautions

: Do not allow large quantities to enter drains or surface waters.

6.3 Methods and materials for : containment and cleaning up

Scrape up and place in a container fitted with a lid. The spilled product produces an

extremely slippery surface.

#### 7. HANDLING AND STORAGE

7.1 Advice on safe handling

General ventilation is recommended. Local ventilation is recommended. Avoid skin and

eye contact. Do not breathe vapour. Do not empty into drains.

7.2 Advice on storage

Do not store with oxidizing agents. Keep container closed and store away from water or

moisture.

Storage temperature: minimum -10 °C, maximum 32 °C

7.3 Specific uses

: Refer to technical data sheet available on request.



According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0

Revision Date: 16.12.2010 Superseded date: 02.03.2010

DOW CORNING(R) 732 MULTI-PURPOSE SEALANT CLEAR

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Name

CAS-No.

**Exposure Limits** 

None of the components have assigned exposure limits.

8.2 Exposure controls

**Engineering Controls** 

Ventilation: Refer to Section 7.1

Personal protection equipment

Respiratory protection

Suitable respiratory protection should be worn if the product is used in large quantities, confined spaces or in other circumstances where the OEL may be approached or exceeded.

Depending on the working conditions, wear a respiratory mask with filter(s) E or use a self-contained respirator.

The choice of a filter type depends on the amount and type of chemical being handled in the workplace. Regarding filter characteristics, contact your respiratory protection

supplier.

Hand protection

Chemical protective gloves should be worn: Butyl rubber. Nitrile rubber. Neoprene rubber. Silver shield(TM). 4H(TM). Viton(TM). Regarding glove's breakthrough time, contact your chemical protective glove supplier.

Eye/face protection

Safety goggles should be worn.

Skin protection

Wear impervious overalls in circumstances where significant skin contact can occur.

Hygiene measures

Exercise good industrial hygiene practice. Wash after handling, especially before eating,

drinking or smoking.

Additional information

These precautions are for room temperature handling. Use at elevated temperature or

aerosol/spray applications may require added precautions.

**Environmental exposure** controls

Refer to section 6 and 12.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form

Paste

Colour

Colorless

Odour

Acetic acid

**Explosive properties** 

No



According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0

Revision Date: 16.12.2010

Superseded date: 02.03.2010

# DOW CORNING(R) 732 MULTI-PURPOSE SEALANT CLEAR

**Specific Gravity** 

1.04

Oxidizing properties

No

The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

## 10. STABILITY AND REACTIVITY

10.1 Reactivity

: Cures in the presence of water or moisture, releasing a small amount of acetic acid.

10.2 Stability

Stable under normal usage conditions.

10.3 Possibility of hazardous

reactions

: None known.

10.4 Conditions to avoid

None established.

10.5 Materials to avoid

Can react with strong oxidising agents. Keep from any possible contact with water.

Protect from moisture

10.6 Hazardous decomposition :

products

Thermal breakdown of this product during fire or very high heat conditions may evolve

the following decomposition products: Silica. Carbon oxides and traces of incompletely

burned carbon compounds. Formaldehyde.

### 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity:

On contact with eyes

Vapour irritates.

On skin contact

Slightly irritating.

If inhaled

The vapour is irritating to the mouth, nose and throat.

On ingestion

Irritant to mucous membranes.

#### Chronic toxicity:

On skin contact

Can irritate on prolonged or repeated skin contact.

If inhaled

Prolonged or repeated inhalation may cause irritation of the upper respiratory system.

On ingestion

Repeated swallowing may cause gastrointestinal irritation and disturbance.

Toxicokinetics, metabolism

and distribution

No specific information is available.

Other Health Hazard

Information

This product contains (a) powder(s) hazardous by inhalation. This is not relevant to the

current physical form of the product, which is not in a respirable form.



According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0

Revision Date: 16.12.2010 Superseded date: 02.03.2010

## DOW CORNING(R) 732 MULTI-PURPOSE SEALANT CLEAR

Based on product test data.

Based on test data from similar products.

## 12. ECOLOGICAL INFORMATION

## 12.1 Ecotoxicity effects

No adverse effects on aquatic organisms are predicted.

## 12.2 Persistence and degradability

Solid material, insoluble in water. No adverse effects are predicted.

#### 12.3 Bioaccumulation

No bioaccumulation potential.

#### 12.4 Release to waters / Mobility in soil

Fate and effects in waste water treatment plants:

No adverse effects on bacteria are predicted.

## 13. DISPOSAL CONSIDERATIONS

Product and packaging disposal

Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

#### 14. TRANSPORT INFORMATION

## Road / Rail (ADR/RID)

Not subject to ADR/RID.

#### Sea transport (IMDG)

Not subject to IMDG code.

#### Air transport (IATA)

Not subject to IATA regulations.



According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0

Revision Date: 16.12.2010 Superseded date: 02.03.2010

## DOW CORNING(R) 732 MULTI-PURPOSE SEALANT CLEAR

#### 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Status

EINECS :

: All ingredients listed, exempt or notified (ELINCS).

**TSCA** 

All chemical substances in this material are included on or exempted from listing on the

TSCA Inventory of Chemical Substances.

**AICS** 

: All ingredients listed, exempt or notified.

**IECSC** 

All ingredients listed or exempt.

KECL

All ingredients listed, exempt or notified.

**PICCS** 

All ingredients listed, exempt or notified.

DSL

: All ingredients listed or exempt.

#### 16. OTHER INFORMATION

This product safety data sheet was prepared in compliance with article 31 and Annex II of the EU REACH Regulation as well as its relevant amendements, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with article 31 and Annex II of the EU REACH Regulation.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.

Source of information: Internal data and publically available information

R14 Reacts violently with water., R22 Harmful if swallowed., R34 Causes burns.

H302 Harmful if swallowed., H314 Causes severe skin burns and eye damage.



According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0

Revision Date: 16.12.2010 Superseded date: 02.03.2010

## DOW CORNING(R) 732 MULTI-PURPOSE SEALANT CLEAR