

EVERBUILD 113 PLUMBERS PUTTY

Colour	Product Code	Pack Size	Box Qty
BEIGE	PLUMB7	750gm	12

Product Description

EVERBUILD PLUMBERS PUTTY is a ready mixed, waterproof; non-setting putty designed for sealing and bedding w/c soil pipes, joints in sanitary wear, sinks and waste water fittings. PLUMBERS' PUTTY will seal ceramics, vitreous enamels, metals and PVC. PLUMBERS PUTTY remains permanently flexible to allow for joint movement, is overpaintable, and is compatible with EVERFLEX Silicone sealants.

Benefits

- Easy to apply by hand
- Non setting - remains permanently elastic
- Added plasticizer improves adhesion and helps prevent cracking.
- Overpaintable

Areas for Use

- Sealing and bedding w/c soil pipes, joints in sanitary wear, sinks and waste water fittings
- Seals ceramics, vitreous enamels, metals and PVC.

Limitations

- When bedding sink/vanity units etc, always finish with a final seal of EVERFLEX SILICONE 500.
- As the manufacturer cannot know all the uses its products may be put to, it is the users responsibility to determine suitability of use. If in doubt, contact Technical Services Department for advice.
- Do not apply below 5°C.

Application

Sealing applications (e.g. W/C soil pipes to pans) – Centralize spigot with untarred hemp. Pack void with PLUMBERS PUTTY and finish with putty knife.

Bedding applications – Place PLUMBERS PUTTY into seating recess and offer up the second component. Trim as required.

In all cases, clean up surfaces by rubbing with a separate piece of PLUMBERS PUTTY. Remove from hands with soap and water.

Specific Data

Appearance	Thick buff paste
Specific Gravity @ 20 °C	2.0 gcm ³ (approx)
Movement Acco	Medium
Application Temp	5°C to 30°C
Service Temp	-30 to 50°C

Health & Safety

Consult MSDS for full list of hazards.

Storage

Store between 5 and 25°C in original unopened containers

Shelf Life

12 months when stored according to manufacturer's instructions.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.