## **Detailed Specifications & Technical Data**



METRIC MEASUREMENT VERSION

ŝ

## 9930 Hook-up/Lead - UL AWM Style 1007

C

For more Information please call

1-800-Belden1



### **Description:**

Tinned copper conductor, PVC insulation. Rated 80°C, 300V. Rated 600V peak for electronic circuits, and internal wiring of electronic and electrical equipment.

Physical Characteristics (Overall)	
Conductor	
AWG: # Conductors AWG Stranding Conductor Materi	al
1 30 7x38 TC - Tinned Coppe	
Insulation	
Insulation Material:	
Insulation Material Wall Thickness (mm) Mi	
PVC - Polyvinyl Chloride0.4060.3	381
Overall Insulation	
Overall Cabling Overall Nominal Diameter:	1.118 mm
Overall Nominal Diameter:	1.110 11111
Mechanical Characteristics (Overall)	
Bulk Cable Weight:	1.786 Kg/Km
Applicable Specifications and Agency	Compliance (Overall)
Applicable Standards & Environmental Pro	
UL AWM Style:	UL Style 1007 (300 V 80°C)
UL Rating:	300 V RMS, 80°C
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2003/11/EC (BFR): CA Prop 65 (CJ for Wire & Cable):	Yes Yes
. ,	
CA Prop 65 (CJ for Wire & Cable):	Yes
CA Prop 65 (CJ for Wire & Cable): Mll Order #39 (China RoHS):	Yes
CA Prop 65 (CJ for Wire & Cable): MII Order #39 (China RoHS): Flame Test	Yes Yes

No related documents are available for this product

**Put Ups and Colors:** 

# **Detailed Specifications & Technical Data**



### METRIC MEASUREMENT VERSION

### 9930 Hook-up/Lead - UL AWM Style 1007

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9930 0011000	305 MT	0.907 KG	BROWN	P	30 STR PVC BRN
9930 002100	30 MT	0.091 KG	RED		30 STR PVC RED
9930 0021000	305 MT	0.907 KG	RED	P	30 STR PVC RED
9930 003100	30 MT	0.091 KG	ORANGE		30 STR PVC ORG
9930 0041000	305 MT	0.907 KG	YELLOW	P	30 STR PVC YEL
9930 005100	30 MT	0.091 KG	GREEN, DARK		30 STR PVC GRN
9930 0051000	305 MT	0.907 KG	GREEN, DARK	P	30 STR PVC GRN
9930 007100	30 MT	0.091 KG	VIOLET		30 STR PVC VIO
9930 008100	30 MT	0.091 KG	GRAY		30 STR PVC GRY
9930 009100	30 MT	0.091 KG	WHITE		30 STR PVC WHT
9930 0091000	305 MT	0.907 KG	WHITE	P	30 STR PVC WHT
9930 010100	30 MT	0.091 KG	BLACK		30 STR PVC BLK
9930 0101000	305 MT	0.907 KG	BLACK	P	30 STR PVC BLK
9930 013100	30 MT	0.091 KG	BLUE, DARK		30 STR PVC DBLU
9930 0131000	305 MT	0.907 KG	BLUE, DARK	P	30 STR PVC DBLU

#### Notes:

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR1 OR 2 STRIPES. 10000' MINIMUM ORDER FOR COLOR COMBINATION.PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL

Revision Number: 2 Revision Date: 10-01-2008

© 2011 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.