Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

34414 Hook-up/Lead - UL AWM Style 3191

*

For more Information please call





Description:

CSPE - Chlorosulphonated Polyethylene insulation has excellent heat resistance, color stability and electrical properties and is recommended for Class 130(B) insulation systems.

Physical Characteristics (Overall)								
Conductor AWG:								
# Conductors AWG Stranding Conductor Material								
1 14 41x30 TC - Tinned Copper								
Insulation								
Insulation Material:								
Insulation Material Wall Thickn	ess (mm)							
CSPE - Chlorosulphonated Polyethylene 1.143								
Overall Insulation								
Overall Cabling								
Overall Nominal Diameter:	4.318 mm							
Applicable Specifications and Agency Co	ompliance (Overall)							
Applicable Standards & Environmental Prog								
UL AWM Style:	3191							
UL Rating:	600 V, 105°C							
CSA Rating:	600 V, 105°C							
СЅА Туре:	CL1053							
EU CE Mark:	Yes							
EU Directive 2000/53/EC (ELV):	Yes							
EU Directive 2002/95/EC (RoHS):	Yes							
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004							
EU Directive 2002/96/EC (WEEE):	Yes							
EU Directive 2003/11/EC (BFR):	Yes							
CA Prop 65 (CJ for Wire & Cable):	Yes							
MII Order #39 (China RoHS):	Yes							
Plenum/Non-Plenum								
Plenum (Y/N):	No							

Related Documents:

No related documents are available for this product

Put Ups and Colors:

ľ	tem #	Putup	Ship Weight	Color	Notes	Item Desc
3	34414 002500	152 MT	6.350 KG	RED	F	#14 STR CSPE 105C 600V
3	34414 005500	152 MT	6.350 KG	GREEN, DARK	F	#14 STR CSPE 105C 600V

Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



34414 Hook-up/Lead - UL AWM Style 3191

34414 0084000	1,219 MT	48.988 KG	GRAY	CIU	#14 STR CSPE 105C 600VRY
34414 008500	152 MT	6.124 KG	GRAY	F	#14 STR CSPE 105C 600V
34414 010100	30 MT	1.497 KG	BLACK		#14 STR CSPE 105C 600V
34414 0104000	1,219 MT	48.988 KG	BLACK		#14 STR CSPE 105C 600V
34414 010500	152 MT	6.124 KG	BLACK	F	#14 STR CSPE 105C 600V

Notes:

C = CRATE REEL PUT-UP.

F = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 50' I = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 200'

U = TOPCOAT ADDERS ON STOCK SOLID COLORS. MINIMUM ORDER 10000' PER COLORCOMBINATION. (SEE TOPCOAT ADDER TABLE)

Revision Number: 1 Revision Date: 01-11-2011

© 2011 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.