Regulation EC No 1907/2006 Art.31

Productname: SILICONE

Ref.Nr.: BDS000341_3_20110620

Creationdate : Replaces:

20.06.11 Version: 1.0

AB10751

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SILICONE

Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Lubricants

1.3. Details of the supplier of the safety data sheet

CRC Industries Europe byba Touwslagerstraat 1 9240 Zele Belgium

Tel.: +32(0)52/45.60.11 Fax.: +32(0)52/45.00.34 E-mail: hse@crcind.com

Subsidiaries		Tel	Fax
CRC Industries Finland Oy	Asemanrinne 13, 08500 Lohja as.	00358/(19)32.921	00358/(19)383.676
CRC Industries France	ZI du Val d'Argent B.P.90028, 12, Bld des Martyrs de Chateaubriant, 95102 Argenteuil Cedex	01.34.11.20.00	01.34.11.09.96
CRC Industries Deutschland GmbH	Südring 9, D-76473 Iffezheim	(07229) 303.0	(07229)30 32 66
CRC INDUSTRIES IBERIA S.L.U.	GREMIO DEL CUERO-PARC.96, POLIGONO INDUSTR. DE HONTORIA, 40195 SEGOVIA	0034/921.427.546	0034/921.436.270
CRC Industries Sweden	Kryptongatan 14, 431 53 Mölndal	0046/31 706 84 80	0046/31 27 39 91

1.4. Emergency telephone number

CRC Industries Europe, Belgium: Tel.: +32(0)52/45.60.11 (office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to 67/548/EEC or 1999/45/EC:

Health: R67: Vapours may cause drowsiness and dizziness.

Physical: EXTREMELY FLAMMABLE

Environment: R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in



Regulation EC No 1907/2006 Art.31

Productname: SILICONE Creationdate: 20.06.11 Version: 1.0

Ref.Nr.: BDS000341_3_20110620 Replaces: AB10751

the aquatic environment.

2.2. Label elements

EXTREMELY FLAMMABLE Warning symbol(s):

Risk-phrase(s): R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

Safety-phrase(s): S2: Keep out of the reach of children.

S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe vapours/spray.

S35: This material and its container must be disposed of in a safe way.

S51: Use only in well-ventilated areas.

Extra label elements according Pressurised container: protect from sunlight and do not expose to temperatures

to Aerosol Dispenser Directive exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a

75/324/EC:

naked flame or any incandescent material.

Without adequate ventilation formation of explosive mixtures may be possible.

2.3. Other hazards

None

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

Hazardous ingredient	CAS-nr.	EC-nr	w/w %	symbol	R-phrases*	Notes
Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	68512-91- 4	270-990- 9	60- 100	F+	12	К
Naphtha (petroleum), hydrotreated light	64742-49- 0	265-151- 9	<20	F,Xn,N	11-38-51/53-65- 67	В,Р
Explanation notes						
B : substance with national established workplace exposure limit						
K : not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)						
P : not classified as carcinogen, less than 0.1% w/w benzene (Einecs-nr. 200-753-7)						

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Naphtha (petroleum), hydrotreated light	01-2119484651- 34	64742- 49-0	265- 151-9	<20	Flam. Liq. 2,Skin Irrit. 2,Asp. Tox. 1,STOT SE 3,Aquatic Chronic 2	H225,H315,H304,H336,H411	В,Р
Explanation notes							



Regulation EC No 1907/2006 Art.31

Productname: SILICONE Creationdate: 20.06.11 Version: 1.0

Ref.Nr.: BDS000341_3_20110620 **Replaces:** AB10751

B: substance with national established workplace exposure limit

P: not classified as carcinogen, less than 0.1% w/w benzene (Einecs-nr. 200-753-7)

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures

4.1. Description of first aid measures

Contact with eyes :	If substance has got into eyes, immediately wash out with plenty of water Seek medical attention if irritation persists
Contact with skin :	Remove contaminated clothing immediately and drench affected skin with plenty of water. Then wash with soap and water Seek medical attention if irritation persists
Inhalation :	Fresh air, keep warm and at rest. Seek medical attention if ill effects occur
Ingestion :	Ingestion is unlikely to occur If swallowed accidentally, do not induce vomiting and seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation: Excessive inhalation of solvent vapours may give rise to nausea, headaches

and dizziness

Ingestion: May induce chemical pneumonia.

Symptoms: sore throat, abdominal pain, nausea, vomiting

Skin contact : May cause irritation.

Symptoms: redness and pain

Eye contact : May cause irritation.

Symptoms: redness and pain

4.3. Indication of any immediate medical attention and special treatment needed

General Advice: If you feel unwell, seek medical advice (show the label where possible

If symptoms persist always call a doctor

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C Forms hazardous decomposition products CO,CO2

5.3. Advice for firefighters



Regulation EC No 1907/2006 Art.31

Productname: SILICONE

20.06.11 Version: 1.0 Creationdate: Ref.Nr.: BDS000341_3_20110620 Replaces: AB10751

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources Ensure adequate ventilation Wear suitable protective clothing and gloves.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material Place in appropriate container

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Equipment should be earthed

Use explosion-proof electrical/ventilating/lighting/?/equipment.

Use only non-sparking tools.

Do not breathe aerosols or vapours.

Ensure adequate ventilation

Avoid contact with skin and eyes.

Wash thoroughly after use

Wear protective gloves/protective clothing/eye protection/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Keep in a cool, dry, well ventilated place

Keep out of reach of children.

7.3. Specific end use(s)

Lubricants



Regulation EC No 1907/2006 Art.31

Productname: SILICONE

20.06.11 Version: 1.0 Creationdate:

Ref.Nr.: BDS000341_3_20110620 Replaces: AB10751

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits:

No information available

8.2. Exposure controls

Control procedures: Ensure adequate ventilation

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Personal protection: Take precautions to avoid contact with skin and eyes when handling the

product.

Ensure adequate ventilation

inhalation: In case of insufficient ventilation, wear suitable respiratory equipment.

Air purifying respirator equiped with organic gas/vapor cartridge (type A or AX)

hands and skin: Wear suitable protective gloves

(nitrile)

eyes: Wear safety goggles.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Propane/butane propelled liquid. Apperance : physical state :

colour: Colorless. odour: Solvent. Not applicable. : Hg Boiling point/range: Not available. < 0 °C Flash point : Not available. Evaporation rate : Explosion limits: upper limit: Not available. lower limit: Not available. Vapour pressure : Not available. Relative density: 0.71 (@ 20°C). Solubility in water: Insoluble in water

> 200 °C Auto-ignition:

Viscosity: < 7 mPa.s (@ 40°C).

9.2. Other information

VOC: 545 g/l

SECTION 10: Stability and reactivity



Regulation EC No 1907/2006 Art.31

Productname: SILICONE

Ref.Nr.: BDS000341_3_20110620

Creationdate : Replaces:

20.06.11 Version: 1.0

AB10751

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation: Inhalation of solvent vapours may give rise to nausea, headaches and

dizziness

Ingestion: May cause gastrointestinal disturbances

Skin contact: Prolonged skin contact will result in defatting of the skin, leading to irritation,

and in some cases, dermatitis

Repeated exposure may cause skin dryness or cracking.

Eye contact: May cause irritation.

Toxicological data:

No information available

SECTION 12: Ecological information

12.1. Toxicity

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



Regulation EC No 1907/2006 Art.31

Productname: SIL

Ref.Nr.:

SILICONE

BDS000341_3_20110620

Creationdate : Replaces:

20.06.11 Version: 1.0

AB10751

Ecotoxicological data:

No information available

12.2. Persistence and degradability

No experimental data available

12.3. Bioaccumulative potential

No experimental data available

12.4. Mobility in soil

Insoluble in water

12.5. Results of PBT and vPvB assessment

No information available

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product : This material and its container must be disposed of in a safe way.

Do not discharge into drains or the environment, dispose to an authorised

waste collection point.

Contaminated packaging: Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number

UN-number: 1950

14.2. UN proper shipping name

Proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es)

Class: 2.1 ADR/RID - Classification code: 5F



Regulation EC No 1907/2006 Art.31

Productname: SILICONE

Ref.Nr.: BDS000341_3_20110620

Creationdate : Replaces:

20.06.11 Version: 1.0

AB10751

14.4. Packing group

Packing group: Not applicable.

14.5. Environmental hazards

No
No
No

14.6. Special precautions for user

ADR/RID - Tunnelcode:	(D)
IMDG - Ems:	F-D,S-U
IATA/ICAO - PAX:	203
IATA/ICAO - CAO	203

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.

Dir. 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

EU-directive 99/45/EC

Regulation (EC) No 1272/2008

Regulation (EC) No 1907/2006 (REACH)

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation risk-phrases: R11: Highly flammable.

R12: Extremely flammable. R38: Irritating to skin.

R65: Harmful: may cause lung damage if swallowed. R67: Vapours may cause drowsiness and dizziness.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

*Explanation hazard statements: H225: Highly flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.



Regulation EC No 1907/2006 Art.31

Productname: SILICONE Creationdate: 20.06.11 Version: 1.0

Ref.Nr.: BDS000341_3_20110620 **Replaces:** AB10751

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

