

Digital Multimeter



Specifications

Basic Functions	Range	Best Accuracy
DC Voltage	200 mV / 2 V / 20 V / 200 V / 1,000 V	$\pm (0.5\% + 2)$
AC Voltage	200 V / 750 V	$\pm (0.8\% + 5)$
DC Current	200 mA / 10 A	
Resistance	200 W / 2 kW / 20 kW / 200 kW / 2 MW / 20 M	
Temperature ($^{\circ}\text{C}$)	-40°C to $1,000^{\circ}\text{C}$	$\pm (2\% + 8)$
Frequency	2 kHz	$\pm (2\% + 5)$
Special Functions		
Fused 10 A range	-	✓
Dwell	4 Cyl / 6 Cyl / 8 Cyl	$\pm (3\% + 5)$
Tach		
Diode	-	✓
Continuity buzzer	-	
Data hold	-	
Low battery display	-	
Input impedance for DC voltage measurement	Around 10 MW	
Maximum display	1,999	

Digital Multimeter



General Characteristics

Power	9 V Battery (6F22)
LCD Size	60 × 54 mm
Product colour	Red meter and grey holster
Product net weight	352 g (Including Holster)
Product size	179 × 88 × 39 mm
Standard accessories	Test lead, battery, English manual, holster, point contact temperature probe
Standard individual packing	Gift box
Standard quantity per carton	40 pieces
Standard carton measurement	598 × 418 × 340 mm (0.085 CBM per standard carton)
Standard carton gross weight	22 kg

* Specifications and other information are subject to change without further

Part Number Table

Description	Part Number
Multimeter, Digital, Automotive, Manual	72-9275

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. TENMA™ is the registered trademark of the Group. © Premier Farnell plc 2011.

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk
www.mcmelectronics.com

