

**BXF SERIES**
**Load Life : 105°C 10000 hours.**
**◆FEATURES**

- 20mm height Max.
- High Ripple Current.
- For Electronic Ballast, Power Supply.
- RoHS compliance.


**◆SPECIFICATIONS**

Items	Characteristics														
Category Temperature Range	-25~+105°C														
Rated Voltage Range	160~450V.DC														
Capacitance Tolerance	±20%(20°C,120Hz)														
Leakage Current(MAX)	$I=0.04CV+100\mu A$ (After 1 minute application of rated voltage) $I=0.02CV+25\mu A$ (After 5 minutes application of rated voltage) $I=(\mu A)$ Leakage Current $C=(\mu F)$ Rated Capacitance $V=(V)$ Rated Voltage														
(tanδ) Dissipation Factor(MAX)	<table border="1"> <thead> <tr> <th>Rated Voltage</th> <th>160</th> <th>200</th> <th>250</th> <th>350</th> <th>400</th> <th>450</th> </tr> </thead> <tbody> <tr> <td>tanδ</td> <td>0.15</td> <td>0.15</td> <td>0.15</td> <td>0.20</td> <td>0.20</td> <td>0.20</td> </tr> </tbody> </table> (20°C,120Hz)	Rated Voltage	160	200	250	350	400	450	tanδ	0.15	0.15	0.15	0.20	0.20	0.20
Rated Voltage	160	200	250	350	400	450									
tanδ	0.15	0.15	0.15	0.20	0.20	0.20									
Endurance	After applying rated voltage with rated ripple current for 10000 hours at 105°C, the capacitors shall meet the following requirement. <table border="1"> <tbody> <tr> <td>Capacitance Change</td> <td>Within ±25% of the initial value.</td> </tr> <tr> <td>Dissipation Factor</td> <td>Not more than 200% of the specified value.</td> </tr> <tr> <td>Leakage Current</td> <td>Not more than the specified value.</td> </tr> </tbody> </table>	Capacitance Change	Within ±25% of the initial value.	Dissipation Factor	Not more than 200% of the specified value.	Leakage Current	Not more than the specified value.								
Capacitance Change	Within ±25% of the initial value.														
Dissipation Factor	Not more than 200% of the specified value.														
Leakage Current	Not more than the specified value.														
Low Temperature Stability Impedance Ratio(MAX)	<table border="1"> <thead> <tr> <th>Rated Voltage</th> <th>160</th> <th>200</th> <th>250</th> <th>350</th> <th>400</th> <th>450</th> </tr> </thead> <tbody> <tr> <td>Z(-25°C)/Z(20°C)</td> <td>3</td> <td>3</td> <td>3</td> <td>6</td> <td>6</td> <td>6</td> </tr> </tbody> </table> (120Hz)	Rated Voltage	160	200	250	350	400	450	Z(-25°C)/Z(20°C)	3	3	3	6	6	6
Rated Voltage	160	200	250	350	400	450									
Z(-25°C)/Z(20°C)	3	3	3	6	6	6									

**◆MULTIPLIER FOR RIPPLE CURRENT**

Frequency Coefficient

(Hz) Frequency		120	1k	10k	100k≤
Coefficient	10~18µF	0.30	0.60	0.90	1.00
	22~82µF	0.40	0.70	0.90	1.00
	100~220µF	0.45	0.75	0.90	1.00

**◆OPTION**


	Code
PET Sleeve	Blank

**◆PART NUMBER**

<u>□□□</u>	<u>BXF</u>	<u>□□□□□</u>	<u>M</u>	<u>□□□</u>	<u>□□</u>	<u>D×L</u>
Rated Voltage	Series	Rated Capacitance	Capacitance Tolerance	Option	Lead Forming	Case Size

◆ **DIMENSIONS**

(mm)



$\phi D$	10	12.5	16	18
$\phi d$	0.6		0.8	
F	5.0		7.5	

◆ **STANDARD SIZE**

Size  $\phi D \times L$ (mm), Ripple Current (mA r.m.s./105°C, 100kHz)

WV(V.DC)	Cap( $\mu F$ )	Size	Ripple
160 (2C)	47	10×16	650
	68	10×20	800
	82	16×16	1350
	100	12.5×20	1350
	100	18×16	1550
	180	16×20	1800
	220	18×20	2250
200 (2D)	33	10×16	650
	47	10×20	800
	56	16×16	1350
	68	12.5×20	1350
	82	18×16	1550
	120	16×20	1800
	180	18×20	2250
250 (2E)	27	10×16	650
	39	10×20	800
	47	16×16	1350
	56	12.5×20	1350
	56	18×16	1550
	100	16×20	1800
	120	18×20	2250

WV(V.DC)	Cap( $\mu F$ )	Size	Ripple
350 (2V)	18	10×16	450
	22	10×20	500
	27	16×16	780
	33	12.5×20	850
	33	18×16	960
	56	16×20	1200
	82	18×20	1300
400 (2G)	12	10×16	450
	18	10×20	500
	18	16×16	780
	27	12.5×20	850
	27	18×16	960
	47	16×20	1200
	56	18×20	1300
450 (2W)	10	10×16	350
	15	10×20	400
	15	16×16	700
	22	12.5×20	700
	22	18×16	850
	33	16×20	970
	47	18×20	1170