FDD / FDFD Series

multicomp

Insulated Crimp Terminals Metric

Female Push-On



Fully Insulated Female Push-On



Features:

- Easy cable entry guide which eliminates flared wire strands
- Bright electrotinned finish which prevents oxidisation
- Full compliance to BS4579, IEC352-2, ISO1996
- A digit is indented above the crimp to verify correct usage

Specifications:

Current Ratings : Quoted at 415 V ac maximum at 32°C

Temperature Range : -20°C to +85°C Insulation : Coloured Vinyl

Terminal : Brass, Copper to BS6017 (1981)
Plating : Electrotinned to BS1872 (1984)

Maximum Electrical Rating : 75°C 300 Volts

Crimp Selection Chart

Wina Dataila	Insulation Colour						
Wire Details	Red	Blue	Yellow				
Wire size in mm ²	0.25 - 1.65	1.04 - 2.63	2.63 - 6.64				
Single standard wire size diameter	0.57 - 1.44	1.14 - 1.82	1.82 - 2.89				
Equivalent A.W.G.	22 - 16	16 - 14	12 - 10				
Equivalent S.W.G.	29 - 17	17 - 13	11 - 6				
	Suitable Met	ric Cables					
	19 / 0.15	19 / 0.3	19 / 0.45				
	13 / 0.2	7 / 0.5	44 / 0.3				
	16 / 0.2	21 / 0.3	7 / 0.85				
	19 / 0.2	30 / 0.25	56 / 0.3				
Otropodod	14 / 0.25	19 / 0.335	65 / 0.3				
Stranded	24 / 0.2	63 / 0.2	37 / 0.4				
	19 / 0.25	1.14 - 1.82 16 - 14 17 - 13 Metric Cables 19 / 0.3 7 / 0.5 21 / 0.3 30 / 0.25 19 / 0.335	159 / 0.2				
	32 / 0.2	35 / 0.3	84 / 0.3				
	40 / 0.2	51 / 0.25	7 / 1.04				
	19 / 0.3	-	-				
Cingle	1 / 0.9	1 / 1.38	1 / 2.25				
Single	1 / 1.13	1 / 1.78	-				

AWG = American Wire Gauge SWG = Standard Wire Gauge

Conductor make up metric cables i.e. 19 / 0.15 = 19 strands of 0.15 mm diameter

www.element14.com www.farnell.com www.newark.com




Dimensions: Millimetres

Page <1> 17/04/12 V1.1

FDD / FDFD Series

multicomp

Insulated Crimp Terminals Metric



Specification Table

Туре	w	а	L	С	В	Т	Current Rating	Colours	Part Number
Female Push-On	5.03	0.5	19.7	1.7	10.5	0.4	10	Red	FDD1-187(5)
	4.9								FDD1-187(8)
	5.03			2.3			15	Blue	FDD2-187(5)
	4.9							Red	FDD2-187(8)
	6.6	0.8	23.5	3.4	13		24	Yellow	FDD5-250
Fully Insulated Female Push-On	-	-	-	-	-	-	15	Blue	FDFD2-250
Double Crimp With Sleeve on Barrel	-	-	-	-	-	-	10	Red	FDD1-110(5)

Dimensions : Millimetres

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.



