



Product Description

| | |
|--------------------------|---|
| Weight | : 10 g (+10% / -5%) |
| Bag Construction | : Tyvek® |
| Flat Dimensions | : 35 × 95 mm (±5%) |
| Silica Gel Specification | : BS7554 : 1992 |
| Printed Message | : Desiccant Silica-gel Do not Eat |

Typical Properties

At 50% RH and 25°C over a period of 4 hours, the moisture uptake equivalent is to 18% of the sachet's total mass the bag construction is designed to limit the shedding of fibres and the silica gel used is a low dust version

Packing Format

100 items per box, and 12 boxes per carton. This gives a carton total of 1,200 items per carton. Within each box the sachets are over-wrapped with a high quality polyethylene to ensure they arrive in active condition. Each pack will contain a humidity indicator card, as an indicator of product quality

Shelf Life

12 Months from date of delivery if stored in a dry warehouse with normal humidity and if packaging remains un-opened. If packaging is opened, use the sachets as soon as possible, and re-seal immediately after use. Dispose of any sachets in re-released packaging, where the humidity indicator has changed from blue to pink

Health and Safety Information

Silica Gel is an amorphous form of silica. In active condition it will release heat when adsorbing water or other substances. If a large quantity of Silica gel quickly adsorbs water, the adsorbent can become hot enough to cause thermal burns of the skin; contact has to be avoided under these conditions. To avoid the risk of explosion in the presence of flammable liquids, gases or dust, earth containers electrically when pouring. Silica Gel should be handled so as to avoid generation of dusty conditions at the workplace. Information to date indicates that the dust is not toxic and does not cause fibrosis. The maximum exposure limit (MEL) in Britain is 6 mg / m³ for total dust in air at the workplace and 3 mg / m³ for respirable dust (< 5 microns). Your national laws may require different dust limits. Please refer to your national laws and regulations if further information is required

Part Number Table

| Description | Part Number |
|----------------------------|-------------|
| Silica Gel, 10 G PK of 100 | PPC198 |

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.