
Header 1 Row, R/Angle, 20 Way








Dimensions : Millimetres

Specifications:

Current rating	: 1A
Voltage rating	: 50V AC/DC
Maximum contact resistance	: 20mΩ
Minimum insulation resistance	: 1,000MΩ
Withstanding voltage	: 500V for one minute
Operating temperature	: -25°C to +105°C

Material:

Insulator	: High temperature Plastic (Nylon PBT)
Standard colour	: Black
Contact	: Copper alloy
Plated	: Gold plated



Part Number Table

Description	Part Number
Header, 1 Row, R/Angle, 20Way	2206RPA-20G

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage resulting from any reliance on the Information or use of it (including liability resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com

