

Transistor, NPN TO-3



Description:

The BUX48/A silicon multi-epitaxial mesa NPN transistors mounted respectively in TO-3 fully isolated package. They are particularly intended for switching and industrial applications from single and three-phase mains
High power NPN silicon transistors

Features:

- High voltage capability
- High current capability
- Fast switching speed

Applications:

Switch mode power supplies
Flyback and forward single transistor low power converters

Absolute Max. Ratings

Parameter	Symbol	Value	Unit
Collector-Emitter Voltage ($R_{BE} = 10\Omega$)	V_{CER}	850	V
Collector-Emitter Voltage ($V_{BE} = 0$)	V_{CES}		
Collector-Emitter Voltage ($I_B = 0$)	V_{CEO}		
Emitter-Base Voltage ($I_C = 0$)	V_{EBO}	7	
Collector Current	I_C	15	A
Collector Peak Current	I_{CM}	30	
Collector Peak Current Non Repetitive ($t_p < 20\mu s$)	I_{CP}	55	
Base Current	I_B	4	
Base Peak Current	I_{BM}	20	
Total Dissipation at $T_C = 25^\circ C$	P_{tot}	175	W
Storage Temperature	T_{stg}	-65 to 200	$^\circ C$
Max. Operating Junction Temperature	T_j	200	

Thermal Data

Characteristic	Symbol	Max.	Unit
Max. Thermal Resistance Junction-case	$R_{thj-case}$	1	$^\circ C/W$

Transistor, NPN TO-3



Electrical Characteristics ($T_{\text{case}} = 25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Test Conditions	Symbol	Min.	Max.	Unit
Collector Cut-off Current ($V_{\text{BE}} = 0$)	$V_{\text{CE}} = \text{rated}$ V_{CES} $V_{\text{CE}} = \text{rated}$ V_{CES} , $T_{\text{C}} = 125^{\circ}\text{C}$	I_{CES}	-	200 2	μA mA
Collector Cut-off Current ($R_{\text{BE}} = 10\Omega$)	$V_{\text{CE}} = \text{rated}$ V_{CER} $V_{\text{CE}} = \text{rated}$ V_{CER} , $T_{\text{C}} = 125^{\circ}\text{C}$	I_{CER}	-	500 4	μA mA
Emitter Cut-off Current ($I_{\text{C}} = 0$)	$V_{\text{EB}} = 5\text{V}$	I_{EBO}	-	1	mA
Collector-Emitter Sustaining Voltage ($I_{\text{B}} = 0$)	$I_{\text{C}} = 200\text{mA}$ $L = 25\text{mH}$	$V_{\text{CEO (sus)*}}$	400	-	V
Emitter-Base Voltage ($I_{\text{C}} = 0$)	$I_{\text{E}} = 50\text{mA}$	V_{EBO}	7	30	
Collector-Emitter Saturation Voltage	$I_{\text{C}} = 10\text{A}$ $I_{\text{B}} = 2\text{A}$ $I_{\text{C}} = 15\text{A}$ $I_{\text{B}} = 4\text{A}$ $I_{\text{C}} = 15\text{A}$ $I_{\text{B}} = 3\text{A}$	$V_{\text{CE (sat)*}}$	-	1.5 3.5 5	
Base-Emitter Saturation Voltage	$I_{\text{C}} = 10\text{A}$ $I_{\text{B}} = 2\text{A}$	$V_{\text{BE (sat)*}}$	-	1.6	

*Pulsed: Pulse Duration = 300 μs , Duty Cycle $\leq 2\%$

Resistive Switching Times

Parameter	Test Conditions	Symbol	Min.	Max.	Unit
Turn-on Time	$V_{\text{CC}} = 150\text{V}$ $I_{\text{C}} = 10\text{A}$ $I_{\text{B1}} = 2\text{A}$	t_{on}	-	1	μs
Storage Time	$V_{\text{CC}} = 150\text{V}$ $I_{\text{C}} = 10\text{A}$ $I_{\text{B1}} = -I_{\text{B2}} = 2\text{A}$	t_{s}	-	3	
Fall Time	$V_{\text{CC}} = 150\text{V}$ $I_{\text{C}} = 10\text{A}$ $I_{\text{B1}} = -I_{\text{B2}} = 1.6\text{A}$	t_{f}	-	0.8	


Inductive Switching Times

Parameter	Test Conditions	Symbol	Min.	Typ.	Max.	Unit
Storage Time	$V_{\text{CC}} = 300\text{V}$ $I_{\text{C}} = 10\text{A}$ $L_{\text{B}} = 3\mu\text{H}$ $V_{\text{BE}} = -5\text{V}$ $I_{\text{B1}} = 2\text{A}$ same conditions at $T_{\text{C}} = 125^{\circ}\text{C}$	t_{s}	-	2.7	5	μs
Fall Time	$V_{\text{CC}} = 300\text{V}$ $I_{\text{C}} = 10\text{A}$ $L_{\text{B}} = 3\mu\text{H}$ $V_{\text{BE}} = -5\text{V}$ $I_{\text{B1}} = 2\text{A}$ same conditions at $T_{\text{C}} = 125^{\circ}\text{C}$	t_{f}	-	0.16	0.4	

Transistor, NPN TO-3




Dimensions



Dimensions	Min.	Max.
A	11 (0.433)	13.1 (0.516)
B	0.97 (0.038)	1.15 (0.045)
C	1.5 (0.59)	1.65 (0.065)
D	8.32 (0.327)	8.92 (0.351)
E	19 (0.748)	20 (0.787)
G	10.7 (0.421)	11.1 (0.437)
N	16.5 (0.649)	17.2 (0.677)
P	25 (0.984)	26 (1.023)
R	4 (0.157)	4.09 (0.161)
U	38.5 (1.515)	39.3 (1.547)
V	30 (1.187)	30.3 (1.193)

Dimensions : Inches (Millimetres)

Internal Schematic Diagram



For TO-3 Package

Part Number Table

Description	Part Number
Transistor, NPN, TO-3	BUX48

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.