



Features & Benefits

- Cat 6A performance
- Suitable for 10-Gigabit Ethernet
- Ultra-slimline design
- LJ6C style module
- Interchangeable with other LJ6C modules and blanks
- Individually QA tested
- Easy to use shield connection

Specification

| | |
|----------------------------|--|
| Width | 25mm |
| Depth | 22mm |
| Height | 38.5mm |
| Recommended Back-box Depth | 32mm |
| Mounting Hole Size | 22mm x 37mm |
| Panel Thickness | 2.0mm max |
| Material | Polycarbonate/ABS thermoplastic resin with grade UL94 VO at 1.5mm flame retardancy |
| Finish | High gloss |
| IDC Labels | Colour coded to T568B |
| Cable Guide | Integrated cable tie position |
| Sockets | High performance shielded RJ45 |
| IDC Blocks | 4 way industry standard IDC blocks |
| Conforms to | ANSI/TIA-568-C.2 Category 6A Specification |

Ordering Information

| Product Description | Part Number |
|------------------------------------|----------------|
| CCS Cat 6A FTP Compact LJ6C Module | 008-000-002-30 |
| LJ6C Single One Gang Faceplate | 008-009-001-00 |
| LJ6C Dual One Gang Faceplate | 008-009-002-00 |
| LJ6C Quad Two Gang Faceplate | 008-009-004-00 |
| Quad Panel for Ackerman Floorbox | 008-011-001-06 |
| LJ6C Blank | 008-001-004-07 |

Connectix Category 6A FTP Modules have been designed to provide the exceptional performance required to support extremely high speed applications such as 10-Gigabit Ethernet.

Connectix LJ6C Modules are ideal for use in floorboxes, or any application that has an industry standard LJ6C aperture. Single and dual gang faceplates are available for up to four LJ6C modules in addition to panels suitable for Ackerman Floorboxes. Their attractive high gloss finish and easy to use labelling system makes them popular with both installers and end users alike. Installation is made easy with the unique colour coded cable saddle and the use of industry standard IDCs.

Connectix Category 6A FTP Modules are fully compliant with the ANSI/TIA Category 6A Standards and provide an outstanding transmission medium free from the problems of alien crosstalk. When used in conjunction with Category 6A FTP Patch Panels and FTP Cable the user will achieve a link performance far exceeding the Category 6A requirements.

