Voltage Regulator Zener Diode





Features:

· Hermetically Sealed, Glass Passivated Silicon Diodes

Specifications:

Zener Voltage Vz Typ : 12V Power Dissipation Pd : 800mW

Operating Temperature Range : -65°C to +175°C

Diode Case Style : SOD-87

No. of Pins : 2

Power Dissipation Max : 2.3W

Termination Type : SMD

Test Current : 50mA

Polarity : Cathode is indicated by a blue band

Absolute Maximum Ratings

| Description | Symbol | Value | Unit | |
|---|------------------|---------------|------|--|
| Power Dissipation T _{tp} = 105°C | P _{tot} | 2.3 | | |
| Power Dissipation PCB mounted T _{amb} = 55°C | P _{tot} | 0.8 | | |
| Non-Repetitive Peak Reverse Power Dissipation t_p = 100 μ s, square pulse; T_j = 25°C prior to surge | P _{zsm} | 300 | W | |
| Non-Repetitive Peak Reverse Power Dissipation; 10/100 μ s, exponential pulse; T_j = 25°C prior to surge | P _{RSM} | 150 | | |
| Storage Temperature | T _{stg} | - 65 to + 175 | °C | |
| Junction Temperature | T _i | - 05 10 + 175 | | |

Thermal Resistance

| Junction to Tie Point | $R_{thj(t-p)}$ | 30 | k/W |
|-----------------------|------------------------|-----|------|
| Junction to Ambient | *R _{th (j-s)} | 150 | K/VV |

^{*} Device mounted on an epoxy glass printed circuit board, 1.5mm thick; thickness of Cu layer ≥40µm Per type when used as Voltage Regulator Diodes



Voltage Regulator Zener Diode



Electrical Characteristics (Ta = 25°C unless specified otherwise) VF <1.2V at 200mA

| Wo Min, | rking Voltag V _z (V) at I _z Nom, | ge Max, | Differential Resistance $r_{\text{diff}}(\Omega)$ at I_z Max. | Coeff S _z (' | erature ficient %/K) t I _z Max. | Test Current at I _z (mA) | Reverse C Reverse I _R at (µA) Max. | |
|------------|---|------------|---|----------------------------|--|---|---|-----|
| 11.4 | 12 | 12.7 | 7 | 0.05 | 0.1 | 50 | 3 | 9.1 |
| 20.8 | 22 | 23.3 | 15 | 0.06 | 0.11 | 25 | 1 | 16 |

Part Number Table

| Description | Part Number | | |
|--------------|-------------|--|--|
| Diado Zanor | BZD27-C12 | | |
| Diode, Zener | BZD27-C22 | | |

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.



