# SAFETY DATA SHEET



#### ARALDITE RAPID RESIN

#### IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE 1. **COMPANY/UNDERTAKING**

Identification of the substance or preparation

: ARALDITE RAPID RESIN **Product name** 

**Product type** : Liquid. **Product description** Preparation

Use of the Component for adhesive applications

substance/preparation

**Supplier** : Huntsman Advanced Materials (Europe)BVBA

Everslaan 45

3078 Everberg / Belgium Tel.: +41 61 299 20 41 Fax: +41 61 299 20 40

**Emergency telephone** 

number

: EUROPE: +32 35 75 1234

France ORFILA: +33(0)145425959

ASIA: +65 6336-6011 China: +86 20 39377888 Australia: 1800 786 152 New Zealand: 0800 767 437

USA: +1/800/424.9300

For further Product EHS related questions concerning this document or its contents, please

contact:

E-Mail:

global\_product\_ehs\_admat@huntsman.com

#### 2. HAZARDS IDENTIFICATION

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : Xi: R36/38

> R43 N: R51/53

Physical/chemical hazards : Not applicable.

**Human health hazards** : Irritating to eyes and skin. May cause sensitisation by skin contact.

**Environmental hazards** : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

See section 11 for more detailed information on health effects and symptoms.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/preparation : Preparation

Ingredient name	CAS number	%	Number	Classification
reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight < 700)	25068-38-6	60 - 100		Xi; R36/38 [1] R43 N; R51/53
butanedioldiglycidyl ether	2425-79-8	3 - 7		Xn; R20/21 [1] Xi; R36/38 R43 R52/53
See section 16 for the full text of the R-phrases declared above				

Date of issue/Date of : 9/7/2009. 1/9

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] PBT-substance
- [4] vPvB-substance

Occupational exposure limits, if available, are listed in section 8.

# 4. FIRST AID MEASURES

#### First-aid measures

Inhalation

: Move exposed person to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Ingestion

: Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Notes to physician

: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

See section 11 for more detailed information on health effects and symptoms.

# 5. FIRE-FIGHTING MEASURES

#### **Extinguishing media**

Suitable

Not suitable

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Special exposure hazards

In a fire or if heated, a pressure increase will occur and the container may burst. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. This material is toxic to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

: No specific data.

Carbon oxides, Burning produces obnoxious and toxic fumes.

Date of issue/Date of : 9/7/2009. 2/9 revision

# 5. FIRE-FIGHTING MEASURES

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## ACCIDENTAL RELEASE MEASURES

#### **Personal precautions**

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

#### **Environmental precautions**

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

# Methods for cleaning up

**Small spill** 

# : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

# 7. HANDLING AND STORAGE

#### Handling

: Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Refer to special instructions/safety data sheet. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

#### **Storage**

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

#### Storage temperature

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Storage temperature: 2 to 40°C (35.6 to 104°F).

Storage hazard class Huntsman Advanced Materials : Storage class 10, Environmentally hazardous liquids

### **Packaging materials**

Recommended

: Use original container.

Date of issue/Date of : 9/7/2009. 3/9 revision

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure limit values**

#### **Ingredient name**

# **Occupational exposure limits**

No exposure limit value known.

# Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

#### **Exposure controls**

# Occupational exposure controls

### : No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

#### **Hygiene measures**

# : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Respiratory protection**

# : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

#### **Hand protection**

: Material of gloves for long term application (BTT>480min):

#### (BTT = Break Through Time)

Ethyl Vinyl Alcohol Laminate (EVAL), butyl rubber

Material of gloves for short term/splash application (10min<BTT<480min):

nitrile rubber, neoprene

Use gloves approved to relevant standards e.g. EN 374 (Europe), F739 (US). Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material and dexterity. Always seek advice from glove suppliers.

Additional information can be found for instance at www.gisbau.de.

#### **Eye protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

#### **Skin protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

# **Environmental exposure controls**

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# **General information**

#### **Appearance**

Physical state : Liquid.
Colour : Yellowish.
Odour : Slight

Important health, safety and environmental information

Date of issue/Date of : 9/7/2009.

revision

4/9

#### ARALDITE RAPID RESIN

# 9. PHYSICAL AND CHEMICAL PROPERTIES

**pH** : 6 [Conc. (% w/w): 50%] Water 20 deg C

Boiling point : >200°C (>392°F)

Flash point : Closed cup: >200°C (>392°F) [DIN 51758 EN 22719 (Pensky-Martens Closed Cup)]

**Decomposition** : >200°C (>392°F)

temperature

**Vapour pressure** : <0.0002 kPa (<0.0015 mm Hg) 20 deg C

Density : 1.17 g/cm³ [25°C (77°F)]
Water solubility : practically insoluble

Viscosity : Dynamic: 25000 to 45000 mPa·s (25000 to 45000 cP) 25 deg C

# 10. STABILITY AND REACTIVITY

**Chemical stability** : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid release to the environment. Refer to special instructions/safety data sheet.
 Materials to avoid : strong acids, strong bases, strong oxidising agents

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

Carbon oxides, Burning produces obnoxious and toxic fumes.

# 11. TOXICOLOGICAL INFORMATION

**Toxicokinetics** 

Absorption: Not available.Distribution: Not available.Metabolism: Not available.Elimination: Not available.

Potential acute health effects

**Inhalation** : No known significant effects or critical hazards.

**Ingestion** : Irritating to mouth, throat and stomach.

**Skin contact**: Irritating to skin. May cause sensitisation by skin contact.

**Eye contact**: Irritating to eyes.

**Acute toxicity** 

Product/ingredient name Result Species Dose Exposure

ARALDITE RAPID RESIN LD50 Oral Rat >5000 mg/kg -

**Conclusion/Summary**: Not available.

Potential chronic health effects

**Chronic toxicity** 

**Conclusion/Summary**: Not available.

**Irritation/Corrosion** 

**Conclusion/Summary**: Not available.

<u>Sensitiser</u>

Product/ingredient name Route of Species Result

exposure

ARALDITE RAPID RESIN skin Guinea pig Sensitising

**Conclusion/Summary** 

Carcinogenicity

: Not available.

0 1 1 10

**Conclusion/Summary**: Not available.

**Mutagenicity** 

**Conclusion/Summary** : Not available.

**Teratogenicity** 

**Date of issue/Date of :** 9/7/2009. **5/9** 

## 11. TOXICOLOGICAL INFORMATION

**Conclusion/Summary** 

: Not available.

Reproductive toxicity

: Not available. Conclusion/Summary

**Chronic effects** Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

Carcinogenicity : No known significant effects or critical hazards. Mutagenicity : No known significant effects or critical hazards. **Teratogenicity** : No known significant effects or critical hazards. : No known significant effects or critical hazards. **Developmental effects Fertility effects** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Inhalation : No specific data. Ingestion : No specific data.

Skin Adverse symptoms may include the following:

> irritation redness

**Eyes** : Adverse symptoms may include the following:

> irritation watering redness

# 12. ECOLOGICAL INFORMATION

**Environmental effects** : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

**Aquatic ecotoxicity** 

Conclusion/Summary : Not available.

**Biodegradability** 

Conclusion/Summary : Not available.

Other adverse effects : No known significant effects or critical hazards.

# 13. DISPOSAL CONSIDERATIONS

Methods of disposal The generation of waste should be avoided or minimised wherever possible. Empty

containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil,

waterways, drains and sewers.

European waste catalogue (EWC)

: The relevant EU Directives and local, regional and national regulations must be complied with. It is among the tasks of the end user to assign the waste to waste codes specific to industrial sectors and processes according to the European Waste catalogue. It is recommended that the details be agreed with the waste disposer

responsible.

070208

07 02 08\* other still bottoms and reaction residues

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

: 9/7/2009. 6/9

Date of issue/Date of revision

## 14. TRANSPORT INFORMATION

#### **International transport regulations**

**Proper shipping name** 

ADR : Environmentally hazardous substance, liquid, n.o.s. BISPHENOL A EPOXY RESIN
 IMDG : Environmentally hazardous substance, liquid, n.o.s. (BISPHENOL A EPOXY RESIN)
 IATA : Environmentally hazardous substance, liquid, n.o.s. (BISPHENOL A EPOXY RESIN)

Regulatory information	UN number	Classes	Packing group	Label	Additional information
ADR/RID Class	UN3082	9	III		Classification code M6 Hazard identification 90 number
IMDG Class	UN3082	9	III		Emergency schedules (EmS) F-A, S-F
IATA Class	UN3082	9	III		Passenger and Cargo Aircraft Quantity limitation: 450 L Packaging instructions: 914 Cargo Aircraft Only Quantity limitation: 450 L Packaging instructions: 914

# 15. REGULATORY INFORMATION

#### **EU regulations**

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

Hazard symbol or symbols



Xi, N Irritant, Dangerous for the environment

Risk phrases : R36/38- Irritating to eyes and skin.

R43- May cause sensitisation by skin contact.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Safety phrases : S24- Avoid contact with skin.

S37- Wear suitable gloves.

S61- Avoid release to the environment. Refer to special instructions/safety data sheet.

**Contains** : reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average

molecular weight < 700) butanedioldiglycidyl ether

butanedioldiglycidyl eti

Exceptional labelling of special preparations

: Contains epoxy constituents. See information supplied by the manufacturer.

Additional warning phrases : Not applicable.

**International regulations** 

Date of issue/Date of : 9/7/2009. 7/9 revision

#### 15. REGULATORY INFORMATION

International lists

Australia inventory (AICS): All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

Japan inventory (ENCS): All components are listed or exempted.

Japan inventory (ISHL): Not determined.

Korea inventory (KECI): All components are listed or exempted.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): All components are listed or exempted.

United States inventory (TSCA 8b): All components are listed or exempted.

**Europe inventory:** All components are listed or exempted. **Canada inventory:** All components are listed or exempted.

# 16. OTHER INFORMATION

Full text of R-phrases referred to in sections 2 and 3 - United Kingdom (UK)

: R20/21- Harmful by inhalation and in contact with skin.

R36/38- Irritating to eyes and skin.

R43- May cause sensitisation by skin contact.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Full text of classifications referred to in sections 2 and 3 - United Kingdom (UK)

: Xn - Harmful Xi - Irritant

N - Dangerous for the environment

#### References

Epoxy Resins and Curing Agents; Toxicology, Health, Safety and Environmental Aspects (Plastics Europe, May 2006) The provision of Safety Data Sheets comes under Regulation 6 of CHIP (CHIP is the recognised abbreviation for the Chemicals Hazard Information and Packaging Regulations). This is an addition to the Health and Safety at Work Act 1974.

Users of products supplied by Huntsman Advanced Materials should take appropriate measures to ensure working practices are in accordance with the Control of Substances Hazardous to Health Regulations (COSHH).

## **History**

Date of printing : 9/7/2009.

Date of issue/ Date of : 9/7/2009.

revision

Date of previous issue : No previous validation.

Version : 1

Indicates information that has changed from previously issued version.

#### Notice to reader

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

Enquiries should be addressed to your nearest Huntsman sales office or to:

Date of issue/Date of : 9/7/2009. 8/9

#### ARALDITE RAPID RESIN

# 16. OTHER INFORMATION

Huntsman Belgium (BVBA) Everslaan 45 B-3078 Everberg Belgium

Tel.:+32-(0)2-758-9211

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.

**Date of issue/Date of** : 9/7/2009. **9/9**