

3 ft Mini DisplayPort™ to DVI Adapter Converter Cable – Mini DP to DVI 1920x1200 - Black

StarTech ID: MDP2DVIMM3B



The MDP2DVIMM3B Mini DisplayPort to DVI Adapter Cable lets you directly connect your Mini DP video source (Desktop PC, Laptop, UltrabookThursday, July 18, 2013 7:53:20 AMrade;, etc.) to a DVI monitor or projector, eliminating the expense of having to upgrade to a Mini DisplayPort-capable monitor.

The adapter cable is 3 feet (1 m) in length, and features male-to-male connectors, allowing you to connect your Mini DisplayPort source directly to a DVI display device with no additional cabling required.

Compatible with Intel® ThunderboltThursday, July 18, 2013 7:53:20 AMrade;, when connected directly to a supporting DisplayPort over Thunderbolt I/O port, the adapter supports resolutions up to 1920x1200 (WUXGA).

MDP2DVIMM3B is a passive adapter that requires a dual-mode DisplayPort port (DisplayPort++), meaning that DVI and HDMI signals can also be passed through the port.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Connect your existing DVI display device (monitor, projector) to a Mini DisplayPort output device
- Ideal for using your DVI monitor as a secondary display

Features

- 1x Male Mini DisplayPort connector, 1x Male DVI connector
- Supports resolutions up to 1920x1200 (WUXGA) and HDTV resolutions up to 1080p
- Compatible with Intel® Thunderbolt™ devices that are capable of outputting a DisplayPort signal



Technical Specifications

Warranty 2 Years Audio No

Chipset ID NXP 3361
Converter Type Passive

Output Signal DVI-D (DVI Digital)

Connector A 1 - Mini-DisplayPort (20 pin) Male

Connector B 1 - DVI-D (25 pin) Male

Maximum Cable Length 915 mm [36 in]

Wide Screen Supported Yes

Maximum Digital 1920x1200 / 1080p

Resolutions

Color Black

Product Height 15 mm [0.6 in]
Product Width 38 mm [1.5 in]
Product Length 920 mm [36.2 in]
Product Weight 75 g [2.6 oz]
Humidity 40%-85%RH

Operating Temperature 0°C to 60°C (32°F to 140°F)
Storage Temperature 0°C to 70°C (32°F to 158°F)

Storage Temperature 0°C to 70°C (32°F to 158°F)

System and Cable DP++ (DisplayPort++) port required from video card or video source for DVI and Requirements HDM® signal pass-through

Shipping (Package) 0.1 kg [0.2 lb]

Weight

Included in Package 1 - Mini DisplayPort® to DVI Adapter

Certifications, Reports and Compatibility





