

# EYNRGBS2

## RBGS Video Cable (4 Coax)

Status: Available

### FUNCTIONAL NOTES:

Cable consisting of (4) 75 ohm coaxial 30 AWG cables twisted together with fiber fillers, with a polyester binder tape, and PVC jacket in accordance with subject 13 for NEC article 725 PLCC cable for general use ( type CL2 ).

### PRODUCT SPECIFICATIONS:

<b>Physical</b>	
<b>Connector One</b>	BNC (Specify gender when ordering)
<b>Connector Two</b>	BNC (Specify gender when ordering)
<b>Application</b>	Video products needing separate RGBS Coax lines
<b>Diameter</b>	0.035 Inch (0.305 cm.)
<b>Wire Gauge</b>	30 AWG Center Conductor
<b>Supported Distance</b>	Per manufacturer's specifications
<b>Shielding</b>	Each conductor has 38 AWG tinned copper braid shield, 90% coverage
<b>Mutual Capacitance</b>	18.5 pF/Ft.
<b>Impedance</b>	75 Ohms
<b>Resistance</b>	0.098 Ohms/Ft. Nominal
<b>Jacket Material</b>	PVC (beige colored)
<b>Jacket Thickness</b>	0.033 Inch
<b>Conductor Material</b>	75 Ohm Coax Cable
<b>Marketing</b>	
<b>Special Product Cross Reference</b>	
<b>Literature</b>	
<b>Manual Available?</b>	
<b>Manual Name</b>	
<b>Manual Date</b>	
<b>Schematic Vendor Name</b>	
<b>Schematic Available?</b>	
<b>Schematic Non-Disclosure Required?</b>	
<b>Schematic Date</b>	
<b>Additional Schematic Requirements</b>	
<b>Literature Comments</b>	