## **MINIATURE LAMP (658) Details**



| Part #              | 658                         |                               |       |                        |                 |
|---------------------|-----------------------------|-------------------------------|-------|------------------------|-----------------|
| Description         | T3 1/4 WEDGE 14V .08A .31CP |                               |       |                        |                 |
| Bulb Shape          | T-3 1/4                     | Filament                      | C-2F  | Base Style             | Wedge (T-3 1/4) |
| Glass Diameter (in) | 0.39                        | $\mathbf{MOL}^{\dagger}$ (in) | 1.06  | LCL <sup>**</sup> (in) | 0.56            |
| Glass Diameter (mm) | 10                          | MOL (mm)                      | 26.80 | LCL (mm)               | 14.20           |
| Volts               | 14                          | MSCP <sup>‡</sup>             | 0.31  | Avg Life Hrs           | 15000           |
| Watts               | 1.12                        | Amps                          | 0.08  | <b>RoHS Compliant</b>  | Yes             |

## + MOL (Maximum Overall Length):

The overall length of a lamp, from the top of the shell to the bottom of the base.

## **‡ MSCP (Mean Spherical Candlepower):**

Candlepower produced at design volts. Candlepower is increased rapidly with an increase of applied voltage and conversely is reduced rapidly with a reduction of applied voltage.

## ++ LCL (Light Center Length):

The distance from a reference point, usually the bottom of the lamp base, to the center of the light source.