

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 25.07.2011 Superseded date: 13.10.2009

DOW CORNING(R) PR-1200 RTV PRIME COAT CLEAR

1. ID	1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY				
1.1	Product name	:	DOW CORNING(R) PR-1200 RTV PI	RIME COAT CLEAR	
1.2	Identified uses	:	Adhesive, binding agents		
	Uses advised against	:	None known.		
1.3	Company	:	Dow Corning Europe S.A. rue Jules Bordet - Parc Industriel - Zone C B-7180 Seneffe Belgium		
	E-mail address (Safety Data Sheet)	:	sdseu@dowcorning.com		
	Customer Service	:	English Deutsch Français Italiano Español	Tel: +49 611237507 Tel: +49 611237500 Tel: +32 64511149 Tel: +32 64511170 Tel: +32 64511163	
1.4	Emergency Phone Number	:	Dow Corning (Barry U.K. 24h) Dow Corning (Wiesbaden 24h) Dow Corning (Seneffe 24h)	Fax: +32 64888683 Tel: +44 1446732350 Tel: +49 61122158 Tel: +32 64 888240	

2. HAZARDS IDENTIFICATION

1.

2.1 Cla	assification	of	the	substance	or	mixture	
---------	--------------	----	-----	-----------	----	---------	--

According to EU Directives 67/548/EEC or 1999/45/EC:

R11 Highly flammable. R65 Harmful: May cause lung damage if swallowed.

...

L DEC D'

2.2 Label elements

T 1 110

Labelling according to EEC Directive					
Contains	: Solvent naphtha (petroleum), light aliph.				
Symbols	: F Highly flammable. Xn Harmful.				
R-phrases	: R11 Highly flammable. R65 Harmful: May cause lung damage if swallowed.				
S-phrases	 S9 Keep container in a well-ventilated place. S16 Keep away from sources of ignition - no smoking. S24/25 Avoid contact with skin and eyes. 				



According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 25.07.2011 Superseded date: 13.10.2009

DOW CORNING(R) PR-1200 RTV PRIME COAT CLEAR

S33 Take precautionary measures against static discharges.S60 This material and its container must be disposed of as hazardous waste.S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

2.3 Other hazards

Vapours may form explosive mixtures with air.



According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 25.07.2011 Superseded date: 13.10.2009

DOW CORNING(R) PR-1200 RTV PRIME COAT CLEAR

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical characterization: Mixture of inorganic and organic compounds

According to EU Directives 67/548/EEC or 1999/45/EC:

Name	CAS-No.	EINECS/ ELINCS No.	REACH Registration Number	Conc. (% w/w)	Classification		
Solvent naphtha (petroleum), light aliph.	64742-89-8	265-192-2	-	85.0	Xn F	R65 R11	
Tetrakis(2-butoxyethyl) orthosilicate	18765-38-3	242-560-0	-	5.0	Xi	R38	
Titanium tetrabutanolate	5593-70-4	227-006-8	-	4.9	Xi	R10 R37/38 R41 R67	
According to Regulation	n (EC) No. 1272	2/2008:					
Name	CAS-No.	EINECS/ ELINCS No.	REACH Registration Number	Conc. (% w/w)	Classification		
Solvent naphtha (petroleum), light aliph.	64742-89-8	265-192-2	-	85.0		Category 2 - H225 Category 1 - H304	
Tetrakis(2-butoxyethyl) orthosilicate	18765-38-3	242-560-0	-	5.0	Skin corrosion/irrita	ation: Category 2 - H315	
Titanium tetrabutanolate	5593-70-4	227-006-8	-	4.9	Skin corrosion/irrita Serious eye damage H318 Specific target orga (Inhalation - vapour irritation) - H335 Specific target orga	Category 3 - H226 ation: Category 2 - H315 s/eye irritation: Category 1 - n toxicity - single exposure r): Category 3 (respiratory tract n toxicity - single exposure r): Category 3 (narcotic effects)	
For the full text of the R-phrases mentioned in this Section, see Section 16. For the full text of the H-Statements mentioned in this Section, see Section 16. CLP classifications are based on all current available data including from known international organizations. These classifications are subject to revision as more information becomes available.							



According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 25.07.2011 Superseded date: 13.10.2009

DOW CORNING(R) PR-1200 RTV PRIME COAT CLEAR

4. FIRST AID MEASURES

4.1	1 Description of First Aid Measures:						
	On contact with eyes	:	Flush with water. If eye irritation persists, consult a specialist.				
	On skin contact	:	Flush with water. If skin irritation persists, get medical attention.				
	If inhaled	:	Remove to fresh air.				
	On ingestion	:	Do not induce vomiting. Obtain medical attention.				
4.2	Most important symptoms/effects, acute and delayed	:	Harmful: May cause lung damage if swallowed.				

5. FIRE-FIGHTING MEASURES

5.1	Suitable extinguishing media	:	On large fires use dry chemical, foam or water spray (fog). On small fires use carbon dioxide (CO2), dry chemical or water spray. Water can be used to cool fire exposed containers.
	Unsuitable extinguishing media	:	None known.
5.2	Hazards during fire fighting	:	Vapours are heavier than air and can travel along ground to remote ignition sources. Electrostatic charges may be generated during transfer of product from its container. Ensure that all equipment is electrically earthed. Vapours may form explosive mixtures with air.
	Hazardous Combustion Products	:	Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.
5.3	Special protective equipment/procedures	:	A self-contained respirator and protective clothing should be worn. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

6. A(. ACCIDENTAL RELEASE MEASURES				
6.1	Personal precautions, protective equipment and emergency procedures	:	A self-contained respirator and protective clothing should be worn. Determine the need to evacuate or isolate the area according to your local emergency plan. Eliminate all possible sources of ignition.		
6.2	Environmental precautions	:	Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers. Do not empty into drains.		
6.3	Methods and materials for containment and cleaning up	:	Determine the need to evacuate or isolate the area according to your local emergency plan. Eliminate all possible sources of ignition. Very large spills should be contained by bunding, etc procedures. Mop, wipe or soak up with absorbent material and place in a container with a lid. The spilled product produces an extremely slippery surface.		



According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 25.07.2011 Superseded date: 13.10.2009

DOW CORNING(R) PR-1200 RTV PRIME COAT CLEAR

7. HANDLING AND STORAGE				
7.1 Advice on safe handling	:	General ventilation is required. Local ventilation is recommended. Avoid skin and eye contact. Do not breathe vapour. Do not ingest. Do not empty into drains.		
7.2 Advice on storage	:	Store in a flameproof, well ventilated area. Electrostatic charges may be generated during transfer of product from its container. Ensure that all equipment is electrically earthed. Keep container tightly closed. Vapours may form explosive mixtures with air. Storage temperature: minimum 0 °C, maximum 35 °C		
7.3 Specific uses	:	Refer to technical data sheet available on request.		

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

-		
Name	CAS-No.	Exposure Limits
Solvent naphtha (petroleum), light aliph.	64742-89-8	10 mg/m3 STEL Oil Mist,mineral 5 mg/m3 TWA Oil Mist,mineral
8.2 Exposure controls		
Engineering Controls	: Ventilation : F	Refer to Section 7.1
Personal protection equipmen	<u>t</u>	
Respiratory protection	confined space exceeded. A suitable resp aerosol or mis Depending on self-contained The choice of	ratory protection should be worn if the product is used in large quantities, es or in other circumstances where the OEL may be approached or pirator must be worn if the product is used in any circumstances where an t may be generated, such as during spraying or similar activities. the working conditions, wear a respiratory mask with filter(s) AP or use a respirator. a filter type depends on the amount and type of chemical being handled in . Regarding filter characteristics, contact your respiratory protection
Hand protection	Silver shield(ective gloves should be worn: Polyvinyl alcohol(PVA). Nitrile rubber. TM). 4H(TM). Viton(TM). Regarding glove's breakthrough time,contact protective glove supplier.
Eye/face protection	: Safety goggle	s should be worn.
Skin protection	: Wear impervi	ous overalls in circumstances where significant skin contact can occur.

DOW CORNING

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 25.07.2011 Superseded date: 13.10.2009

DOW CORNING(R) PR-1200 RTV PRIME COAT CLEAR

Hygiene measures	:	Exercise good industrial hygiene practice. Wash after handling, especially before eating, drinking or smoking.
Additional information	:	These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions. For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these types of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group.
<u>Environmental exposure</u> <u>controls</u>	:	Refer to section 6 and 12.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: Liquid			
Colour	: Colorless to pale yellow			
Odour	: Solvent odor.			
Boiling point/range	: >80 °C			
Flash point	: 13 °C (Tag Closed Cup)			
Explosive properties	: No Vapours may form explosive mixtures with	air.		
Specific Gravity	: 0.76			
Viscosity	: 1 mm2/s at 25°C.			
Oxidizing properties	: No			

The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

10. STABILITY AND REACTIVITY				
10.1 Reactivity	:	None known.		
10.2 Stability	:	Stable under normal usage conditions.		
10.3 Possibility of hazardous reactions	:	None known.		
10.4 Conditions to avoid	:	Eliminate all possible sources of ignition.		
10.5 Materials to avoid	:	Can react with strong oxidising agents.		
10.6 Hazardous decomposition products	:	Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.		
		6 of 10		

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 25.07.2011 Superseded date: 13.10.2009

DOW CORNING(R) PR-1200 RTV PRIME COAT CLEAR

11. TOXICOLOGICAL INFO	RMA	TION
Acute toxicity:		
On contact with eyes	:	Slightly irritating.
On skin contact	:	Slightly irritating.
If inhaled	:	Single exposure may cause transient drowsiness and dizziness.
On ingestion	:	May be fatal if swallowed and enters airways.
Chronic toxicity:		
On skin contact	:	Repeated or prolonged contact may cause defatting of the skin, leading to dermatitis. Can irritate on prolonged or repeated contact.
If inhaled	:	May cause dizziness, drowsiness, confusion, headaches, nausea, and at high concentrations, unconsciousness.
On ingestion	:	Smallest quantities reaching the lungs through swallowing or subsequent vomiting may result in lung oedema or pneumonia. Repeated swallowing may cause systemic adverse effects.
Toxicokinetics, metabolism and distribution	:	No specific information is available.
¹ Based on product test d ² Based on test data from		ar products.

12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity effects

No adverse effects on aquatic organisms are predicted.

12.2 Persistence and degradability

The mineral oils in the product are biodegradable. Organic solvents may evaporate into the atmosphere, where they degrade.

12.3 Bioaccumulation

No specific information is available.

12.4 Release to waters / Mobility in soil

Fate and effects in waste water treatment plants:



According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 25.07.2011 Superseded date: 13.10.2009

DOW CORNING(R) PR-1200 RTV PRIME COAT CLEAR

No adverse effects on bacteria are predicted.

13. DISPOSAL CONSIDERATIONS				
Product and packaging disposal	:	Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.		

14. TRANSPORT INFORMATION

<u>Road / Rail (ADR/RID)</u>	
UN No.	: UN 1993
Proper Shipping Name	: FLAMMABLE LIQUID, N.O.S.(Petroleum distillates / Tetrabutyl titanate)
Class	: 3
Packing group	: II
Labels	: 3
<u>Sea transport (IMDG)</u>	
UN No.	: UN 1993
Proper Shipping Name	: FLAMMABLE LIQUID, N.O.S.(Petroleum distillates / Tetrabutyl titanate)
Class	: 3
Packing group	: П
Emergency Schedule (EmS)	: F-E S-E
Labels	: flammable liquid
<u>Air transport (IATA)</u>	
UN No.	: UN 1993
Proper Shipping Name	: Flammable liquid, n.o.s.(Petroleum distillates / Tetrabutyl titanate)
Class	: 3
Packing group	: П
Labels	: Flammable Liquid



According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 25.07.2011 Superseded date: 13.10.2009

DOW CORNING(R) PR-1200 RTV PRIME COAT CLEAR

5.1 Safety, health	and environmental regulations/legislation specific for the substance or mixture
<u>Status</u>	
EINECS	: All ingredients listed, exempt or notified (ELINCS).
TSCA	: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.
IECSC	: All ingredients listed or exempt.
PICCS	: All ingredients listed, exempt or notified.
DSL	: Consult your local Dow Corning office.
AICS	: Consult your local Dow Corning office.
KECL	: One or more ingredients are not listed or exempt or identified.

DOW CORNING

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 25.07.2011 Superseded date: 13.10.2009

DOW CORNING(R) PR-1200 RTV PRIME COAT CLEAR

16. OTHER INFORMATION

This product safety data sheet was prepared in compliance with article 31 and Annex II of the EU REACH Regulation as well as its relevant amendements, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with article 31 and Annex II of the EU REACH Regulation.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.

Source of information: Internal data and publically available information

R10 Flammable., **R11** Highly flammable., **R37/38** Irritating to respiratory system and skin., **R38** Irritating to skin., **R41** Risk of serious damage to eyes., **R65** Harmful: May cause lung damage if swallowed., **R67** Vapours may cause drowsiness and dizziness.

H225 Highly flammable liquid and vapour., H226 Flammable liquid and vapour., H304 May be fatal if swallowed and enters airways., H315 Causes skin irritation., H318 Causes serious eye damage., H335 May cause respiratory irritation., H336 May cause drowsiness or dizziness.