



## Quick-Connect Surge Protector, 4-Wire RS-232

# Get convenient quick-connect surge protection for RS-232 Ethernet 4-wire connections.

Put avalanche diode protection where you need it.



### Specifications

**Application:** RS-232 / digital 4-20 mA Current Loop

**Ground Wire:** Yes

**Maximum Shunt Capacitance:** <40 pF

**Peak Pulse Current:** 60 amps

**Pins Protected:** All

**Protection Type:** Avalanche diode technology

**Response Time:** <5 ns

**Standard Clamping Voltage:** 18 volts

**Connectors:** 4-position terminal block (14 to 26 AWG)

### Overview

This quick-connect surge protector guards Ethernet 4-wire RS-232 connections.

### What's included

- Quick-Connect Surge Protector
- Specification sheet

© Copyright 2010. Black Box Corporation. All rights reserved. Printed in U.S.A. Black Box® and the Double Diamond logo are registered trademarks of BB Technologies, Inc. Double Diamond™ is a trademark of BB Technologies, Inc. Any third-party trademarks appearing in this publication are acknowledged to be the property of their respective owners.

SP602A, rev. 1

### Customer Support Information

Order toll-free in the U.S.: Call 877-877-BBOX (outside U.S. call 724-746-5500)  
 FREE technical support 24 hours a day, 7 days a week: Call 724-746-5500 or fax 724-746-0746  
 Mailing address: Black Box Corporation, 1000 Park Drive, Lawrence, PA 15055-1018  
 Web site: [www.blackbox.com](http://www.blackbox.com) • E-mail: [info@blackbox.com](mailto:info@blackbox.com)