WAGO Communication Cable

The WAGO communication cable offers a simple solution for communicating with the WAGO software tools (e.g., WAGO-I/O-CHECK 2, WAGO-I/O-PRO)

NOTICE: The communication cable must not be connected or removed when the system is energized.

The WAGO USB Service Cable connects a PC (notebook) to either the service Interface of the 857 Series Signal Conditioners and Relay Modules (JUMPFLEX) or to WAGO-I/O-SYSTEM buscouplers/controllers.

Notice:
Using the WAGO 759-923 USB Service Cable in combination with some of the programmable fieldbus controllers requires a certain firmware version or higher:
750-841 as from firmware version 12
750-872/0020-0000 as from firmware version 2

Description	Item no.	Pack. unit
Communication cable	**750-920**	1

Technical Data

Connection	4-pole service connectors
Operating temperature	0 °C ... +55 °C
Degree of protection	IP20
Length	2.5 m
Connector dimensions (WxHxD)	15 x 50 x 19 mm

Description	Item no.	Pack. unit
WAGO USB Service Cable	**750-923**	1

Technical Data

USB specification	2.0 compatible/full-speed device
Operating system	Windows 98/2000/XP/VISTA
Operating temperature	-25 °C ... +70 °C
Interface USB	type A/m
Length	2.5 m
Connector dimensions (WxHxD)	15 x 50 x 19 mm
Test voltage	2.5 kV, 50 Hz, 1 min.
Conformity marking	CE
Immunity to interference	acc. to EN 61000-4-3, EN 61000-4-6
Emission of interference	acc. to EN 55022

WAGO Kontakttechnik GmbH & Co. KG
Postfach 2880 • D-32385 Minden Tel.: +49(0)571/887-0 E-Mail: info@wago.com
Hansastr. 27 • D-32423 Minden Fax: +49(0)571/887-169 www.wago.com