

# UL1061 - 18AWG PVC Hook-Up Wire

## 100m, 152.5m reel



**Product Code:** UL1061 PVC Hook-Up Wire

### Product Description:

#### Application

Internal wiring of appliances where exposed to oil at temperature not exceeding 60°C.

#### Multi-construction

- Single

### Construction:

Conductor Material : Tinned copper  
 Conductor AWG : 18  
 Conductor Construction : T0.4±0.005×7 (7×26AWG)  
 Conductor Stranded Dia.(mm) : 1.22  
 Jacket Material : Semi-Rigid PVC  
 Jacket Min. Thickness : 0.25  
 Jacket Dia.(mm) : 1.73±0.1  
 Jacket Colour : See Table Below

#### Packaging


- 100m and 152.5m reel

### Electrical Characteristics:

Max. Conductor DC Resistance at 20°C (Ω/Km) : <21.16  
 Rated Temperature (°C) AWM/Style 1061 : 80  
 Rated Voltage (V) : 300  
 20°C Insulation Resistance(MΩ.KM) : >200

### Part Number Table

#### Diagram:



Description	Colour	Reel Length (m)	Part Number
18AWG 7/26 UL1061	Black	100	PP000228
	Blue		PP000229
	Brown		PP000230
	Grey		PP000231
	Red		PP000232
	White		PP000233
	Yellow		PP000234
	Green/Yellow		PP000235
	Black	152.5	PP000236

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

