



# Material Safety Data Sheet Water MSDS

### **Section 1: Chemical Product and Company Identification**

Product Name: Water

Catalog Codes: SLW1063

CAS#: 7732-18-5

RTECS: ZC0110000

TSCA: TSCA 8(b) inventory: Water

CI#: Not available.

Synonym: Dihydrogen oxide

Chemical Name: Water

**Chemical Formula: H2O** 

**Contact Information:** 

Sciencelab.com, Inc. 14025 Smith Rd. Houston, Texas 77396

US Sales: 1-800-901-7247

International Sales: 1-281-441-4400

Order Online: ScienceLab.com

CHEMTREC (24HR Emergency Telephone), call:

1-800-424-9300

International CHEMTREC, call: 1-703-527-3887

For non-emergency assistance, call: 1-281-441-4400

### **Section 2: Composition and Information on Ingredients**

### Composition:

Name	CAS#	% by Weight
Water	7732-18-5	100

Toxicological Data on Ingredients: Not applicable.

### **Section 3: Hazards Identification**

#### **Potential Acute Health Effects:**

Non-corrosive for skin. Non-irritant for skin. Non-sensitizer for skin. Non-permeator by skin. Non-irritating to the eyes. Non-hazardous in case of ingestion. Non-hazardous in case of inhalation. Non-irritant for lungs. Non-sensitizer for lungs. Non-corrosive to the eyes. Non-corrosive for lungs.

#### **Potential Chronic Health Effects:**

Non-corrosive for skin. Non-irritant for skin. Non-sensitizer for skin. Non-permeator by skin. Non-irritating to the eyes. Non-hazardous in case of ingestion. Non-hazardous in case of inhalation. Non-irritant for lungs. Non-sensitizer for lungs. CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available.

### **Section 4: First Aid Measures**

Eye Contact: Not applicable.

Skin Contact: Not applicable.

Serious Skin Contact: Not available.

**Inhalation:** Not applicable.

Serious Inhalation: Not available.

**Ingestion:** Not Applicable

Serious Ingestion: Not available.

### **Section 5: Fire and Explosion Data**

Flammability of the Product: Non-flammable.

Auto-Ignition Temperature: Not applicable.

Flash Points: Not applicable.

Flammable Limits: Not applicable.

**Products of Combustion:** Not available.

Fire Hazards in Presence of Various Substances: Not applicable.

Explosion Hazards in Presence of Various Substances: Not Applicable

Fire Fighting Media and Instructions: Not applicable.

Special Remarks on Fire Hazards: Not available.

Special Remarks on Explosion Hazards: Not available.

### **Section 6: Accidental Release Measures**

Small Spill: Mop up, or absorb with an inert dry material and place in an appropriate waste disposal container.

Large Spill: Absorb with an inert material and put the spilled material in an appropriate waste disposal.

### Section 7: Handling and Storage

**Precautions:** No specific safety phrase has been found applicable for this product.

Storage: Not applicable.

### **Section 8: Exposure Controls/Personal Protection**

**Engineering Controls:** Not Applicable

Personal Protection: Safety glasses. Lab coat.

Personal Protection in Case of a Large Spill: Not Applicable

**Exposure Limits:** Not available.

### **Section 9: Physical and Chemical Properties**

Physical state and appearance: Liquid.

Odor: Odorless.

Taste: Not available.

Molecular Weight: 18.02 g/mole

Color: Colorless.

pH (1% soln/water): 7 [Neutral.]

Boiling Point: 100°C (212°F)

Melting Point: Not available.

Critical Temperature: Not available.

Specific Gravity: 1 (Water = 1)

Vapor Pressure: 2.3 kPa (@ 20°C)

**Vapor Density:** 0.62 (Air = 1)

Volatility: Not available.

Odor Threshold: Not available.

Water/Oil Dist. Coeff.: Not available. Ionicity (in Water): Not available.

**Dispersion Properties:** Not applicable

Solubility: Not Applicable

### **Section 10: Stability and Reactivity Data**

Stability: The product is stable.

Instability Temperature: Not available.Conditions of Instability: Not available.

Incompatibility with various substances: Not available.

Corrosivity: Not available.

Special Remarks on Reactivity: Not available.

Special Remarks on Corrosivity: Not available.

Polymerization: Will not occur.

### **Section 11: Toxicological Information**

Routes of Entry: Absorbed through skin. Eye contact.

**Toxicity to Animals:** 

LD50: [Rat] - Route: oral; Dose: > 90 ml/kg LC50: Not available.

Chronic Effects on Humans: Not available.

Other Toxic Effects on Humans:

Non-corrosive for skin. Non-irritant for skin. Non-sensitizer for skin. Non-permeator by skin. Non-hazardous in case of ingestion. Non-hazardous in case of inhalation. Non-irritant for lungs. Non-sensitizer for lungs. Non-corrosive to the eyes. Non-corrosive for lungs.

**Special Remarks on Toxicity to Animals:** Not available.

Special Remarks on Chronic Effects on Humans: Not available.

Special Remarks on other Toxic Effects on Humans: Not available.

### **Section 12: Ecological Information**

**Ecotoxicity:** Not available.

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The product itself and its products of degradation are not toxic.

Special Remarks on the Products of Biodegradation: Not available.

### **Section 13: Disposal Considerations**

#### Waste Disposal:

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

### **Section 14: Transport Information**

DOT Classification: Not a DOT controlled material (United States).

Identification: Not applicable.

Special Provisions for Transport: Not applicable.

### **Section 15: Other Regulatory Information**

Federal and State Regulations: TSCA 8(b) inventory: Water

Other Regulations: EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

Other Classifications:

WHMIS (Canada): Not controlled under WHMIS (Canada).

DSCL (EEC):

This product is not classified according to the EU regulations. Not applicable.

HMIS (U.S.A.):

Health Hazard: 0

Fire Hazard: 0

Reactivity: 0

Personal Protection: a

National Fire Protection Association (U.S.A.):

Health: 0

Flammability: 0

Reactivity: 0

Specific hazard:

### **Protective Equipment:**

Not applicable. Lab coat. Not applicable. Safety glasses.

### **Section 16: Other Information**

References: Not available.

Other Special Considerations: Not available.

Created: 10/10/2005 08:33 PM

**Last Updated:** 05/21/2013 12:00 PM

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall ScienceLab.com be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ScienceLab.com has been advised of the possibility of such damages.



Chicago, IL 60640-4496 Phone: (773) 907-5181 Fax: (773) 907-5180

E-mail (techsupport@spctechnology.com)

Doc. No.: MSDS-034 DCP No.: 1955 Effective Date: 3/19/08

## **Material Safety Data Sheet**

Emergency/Information: (800) 420-8021

### Section 1 - Product Information

**PRODUCT NAME:** No Clean Solder Wire - LF965-30 (Sn96.5/Ag3.0/Cu0.5)

**PRODUCT DESCRIPTION:** No Clean Solder Wire

**PRODUCT CODE:** SPC22157

### Section 2 – Composition/Information on Ingredients

<b>Chemical Name</b>	Wt%	CAS	EINECS
Tin*	92.3 - 96.2	7440-31-5	231-141-8
Silver*	2.7 - 3.2	7440-22-4	231-131-3
Copper *	0.3 - 0.7	7440-50-8	231-159-6

<sup>\*</sup>Exact weight percentages can be determined from the product label

### Section 3 – Hazards Identification

#### POTENTIAL HEALTH EFFECTS

**EYES**: Fumes from this and other soldering products may cause eye irritation.

**SKIN**: Fumes from this and other soldering products may cause skin irritation.

**INGESTION:** Ingestion of this or other soldering products may cause headache, nausea, and muscular pain.

**INHALATION**: Inhalation of the fumes from this or other soldering products may cause headache, nausea and muscular pain.

### SIGNS AND SYMPTOMS OF OVEREXPOSURE

SKIN: Discomfort or rash.

**INHALATION**: Irritation of the pulmonary system.

CHRONIC: Prolonged or repeated exposure due to ingestion may cause anemia, insomnia, weakness,

constipation and abdominal pain.

Prolonged or repeated exposure due to skin exposure and inhalation may cause skin rash and

damage to the mucous membranes.

**CARCINOGENICITY**: Not listed as a carcinogen by NTP, OSHA, or ACGIH.

MEDICAL CONDITIONS AGGRAVATED: Pre-existing conditions of the lungs, kidneys, nervous system and

possibly reproductive systems; diseases of the blood forming organs

**ROUTES OF ENTRY**: Inhalation, ingestion, eye or skin contact



Chicago, IL 60640-4496 Phone: (773) 907-5181 Fax: (773) 907-5180

E-mail (techsupport@spctechnology.com)

Doc. No.: MSDS-034 DCP No.: 1955 Effective Date: 3/19/08

## **Material Safety Data Sheet**

Emergency/Information: (800) 420-8021

## Section 4 - First Aid Measures

### EYES:

MOLTEN PRODUCT: Cool burns with plenty of low-pressure water. Get immediate medical attention.

SOLID PRODUCT: Remove any contact lenses. Immediately flush eyes with large quantities of water for at least 15 minutes. Get medical attention if irritation develops.

### SKIN:

MOLTEN PRODUCT: Immediately cool skin burns with water and cold packs for at least 15 minutes. Do not put ice directly on the skin.

Do not attempt to remove solidified product from the skin, as damage may result. Get immediate medical attention.

**SOLID PRODUCT:** 

Immediately wash skin with soap and copious amounts of water. Use lotion to prevent dryness. Get medical attention if irritation develops.

**INGESTION**: If person is conscious, immediately give 2 glasses of water. Do not induce vomiting. Get immediate medical attention.

**INHALATION**: If symptoms of overexposure are experienced, evacuate to fresh air. If symptoms persist, seek medical attention.

**COMMENTS**: If victims of chemical over-exposure are taken for medical attention, give a copy of the label or this MSDS to the physician/health care professional.

### <u>Section 5 – Fire Fighting Measures</u>

FLASHPOINT AND METHOD: Not Applicable

FLAMMABLE LIMITS: Not Established

**AUTOIGNITION TEMPERATURE**: Not Applicable

**EXTINGUISHING MEDIA**: Alcohol foam, carbon dioxide, or dry chemical.

**EXPLOSION HAZARDS**: Closed containers may explode when exposed to fire conditions.

**FIRE FIGHTING EQUIPMENT**: Self contained breathing apparatus with full face piece operated in positive pressure demand mode, appropriate turn-out gear and chemical resistant personal protective equipment is recommended.



Chicago, IL 60640-4496 Phone: (773) 907-5181 Fax: (773) 907-5180

E-mail (techsupport@spctechnology.com)

Doc. No.: MSDS-034 DCP No.: 1955 Effective Date: 3/19/08

## **Material Safety Data Sheet**

Emergency/Information: (800) 420-8021

### <u>Section 6 – Accidental Release Measures</u>

**GENERAL PROCEDURES**: If the material is in its solid state, pick up and reuse. When molten, allow to solidify, and then reuse if it is not contaminated. If contaminated, refer to Section 13 for proper disposal procedures.

**RELEASE NOTES**: Avoid repeated or prolonged breathing or skin contact. Wash hands immediately, and remove material from under the fingernails.

### Section 7 – Handling and Storage

**GENERAL PROCEDURES**: Do not store or use near sparks or open flames. Keep containers tightly closed and upright when not in use in order to prevent leakage.

### Section 8 – Exposure Controls / Personal Protection

## **Exposure Guidelines OSHA Hazardous Components (29 CFR 1910.1200)**

		OSHA PEL	ACGIH TLV	Supplier OEL	
		ppm mg/m3	ppm mg/m3	ppm mg/m3	
Tin*	TWA	$NL^{[1]}2.00$	NL 2.00	NL NL	
	STEL	NL NL	NL NL	NL NL	
Silver *	TWA	NL 0.10	NL 0.10	NL NL	
	STEL	NL NL	NL NL	NL NL	
Copper*	TWA	NL 0.20	NL 0.20	NL NL	
	STEL	NL NL	NL NL	NL NL	

<sup>\*</sup>Exact weight percentages can be determined from the product label

#### **OSHA Table Comments**

1. NL = Not Listed

**ENGINEERING CONTROLS**: General (mechanical) room ventilation is expected to be satisfactory where this product is stored and handled and in closed equipment. Special local ventilation is needed at points where vapors can be expected to escape into the workplace air.

### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE**: Face shield, safety glasses with side shield or chemical splash goggles. When working with molten material, face shield is recommended.

**SKIN**: Rubber, chemical resistant gloves. When material is heated, wear gloves to protect against thermal burns.

**RESPIRATORY**: Not normally needed in well ventilated areas. If the ventilation is insufficient to remove smoke from soldering processes, use NIOSH/MSHA approved cartridge type respirator.



Chicago, IL 60640-4496 Phone: (773) 907-5181 Fax: (773) 907-5180

E-mail (techsupport@spctechnology.com)

#### Doc. No.: MSDS-034 DCP No.: 1955 Effective Date: 3/19/08

## **Material Safety Data Sheet**

Emergency/Information: (800) 420-8021

PROTECTIVE CLOTHING: Protective clothing and safety shoes as necessary to minimize contact.

WORK HYGIENIC PRACTICES: Good personal hygiene practices should be used. Wash after any contact, before eating, and at the end of the work period.

**OTHER USE PRECAUTIONS**: Eye wash station and quick drench safety shower in immediate work area.

### Section 9 – Physical and Chemical Properties

**ODOR**: Odorless

**APPEARANCE**: Metal in wire form.

**COLOR**: Silver gray

VAPOR PRESSURE: 1 mmHg at 866 °C (1591 °F)

**VAPOR DENSITY**: Not Determined

**BOILING POINT**: 1380 °C (2516 °F)@ 760 mmHg

**MELTING POINT**: 183 °C (361 °F)(alloy) **SOLUBILITY IN WATER:** Partially Soluble

### Section 10 - Stability and Reactivity

STABILITY: Stable under ordinary use and storage conditions.

**POLYMERIZATION**: Will not occur under normal use and storage conditions.

HAZARDOUS DECOMPOSITION PRODUCTS: May emit toxic fumes of carbon monoxide and carbon

dioxide.

MSDS-034

**INCOMPATIBLE MATERIALS**: Strong acids and strong oxidizers should be avoided.

### <u>Section 11 – Toxicological Information</u>

**GENERAL COMMENTS**: No toxicological information available at this time.

### Section 12 – Ecological Information

**GENERAL COMMENTS**: No information on ecological toxicity or biodegradability is available at this time.

## Section 13 – Disposal Considerations

**DISPOSAL METHOD:** Dispose of this material, contaminated absorbent material and other contaminated materials in an approved waste disposal facility, according to all applicable Federal, State, and Local regulations. Recovery and reuse, rather than disposal, should be the ultimate goal in handling efforts.



Chicago, IL 60640-4496 Phone: (773) 907-5181 Fax: (773) 907-5180

E-mail (techsupport@spctechnology.com)

Doc. No.: MSDS-034 DCP No.: 1955 Effective Date: 3/19/08

## **Material Safety Data Sheet**

Emergency/Information: (800) 420-8021

### **14. Transport Information**

**DOT (DEPARTMENT OF TRANSPORTATION)** 

**PROPER SHIPPING NAME**: Not regulated by DOT

**CANADA TRANSPORT OF DANGEROUS GOODS** 

PROPER SHIPPING NAME: Not regulated

AIR (ICAO/IATA)

PROPER SHIPPING NAME: Not regulated

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Not regulated

### 15. Regulatory Information

**UNITED STATES** 

### SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Chronic health hazard.

313 REPORTABLE INGREDIENTS: Lead CAS# 7439-92-1 (weight percentage can be determined from product label)

### CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)


**CERCLA REGULATORY**: As a solid in wire form, there in no reportable quantity (RQ) for this product. However, if it is cut into pieces smaller than 100 micrometers, the RQ for silver is 1000 lbs., and the RQ for copper is 5000 lbs. Please contact local authorities to determine if there are any local reporting requirements.

### TSCA (TOXIC SUBSTANCE CONTROL ACT)

**TSCA STATUS**: All ingredients are listed or are exempt from listing (as polymers) on the Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

**CALIFORNIA PROPOSITION 65**: When used for soldering and similar applications chemicals may be produced which are known to some states to cause birth defects or other reproductive harm.

### 16. Other Information





4801 North Ravenswood Avenue Chicago, IL 60640-4496

Phone: (773) 907-5181 Fax: (773) 907-5180

E-mail (techsupport@spctechnology.com)

Doc. No.: MSDS-034 DCP No.: 1955 Effective Date: 3/19/08

## **Material Safety Data Sheet**

Emergency/Information: (800) 420-8021

MANUFACTURER DISCLAIMER: The information contained herein is based upon data considered to be accurate and is offered solely for information, customer consideration and investigation. The manufacturer extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The content of this Material Safety Data Sheet relates only to this product as sold and does not relate to use with any other material or in any process. All chemical products should be used only by, or under, the direction of technically qualified personnel, who are aware of the hazards involved and of the necessity for reasonable care in handling. Hazard communication regulations, United States Occupational Health and Safety (OSHA) and Canadian Workplace Hazardous Materials Information System (WHMIS) require that employees must be trained in the use of Material Safety Data Sheets as a source of hazards information and response.

MSDS-034



# **Material Safety Data Sheet**

Revision Date Prepared by Technical Information

November 19, 2013 Patti Rogers, MH 1-800-201-8822 or <a href="mailto:support@mgchemicals.com">support@mgchemicals.com</a> **Head Office**T-800-201-8822 or <a href="mailto:support@mgchemicals.com">support@mgchemicals.com</a>

9347 - 193 Street, Surrey, B.C., V4N 4E7 Phone Canutech (613) 996-6666 Collect 24 hrs

For updates please download from www.mgchemicals.com or fax requests to 1-800-708-9888

### **Section 1: Product Identification**

MSDS Code: 4900 Name: Lead Free Solder

Related Part Numbers: 4900-35G, 4900-112G, 4900-227G, 4900-454G

Use: Soldering

#### **Section 2: Hazardous Ingredients**

CAS#	<b>Chemical Name</b>	Percentage by weight	ACGIH TWA	Osha Pel	Osha Stel
7440-50-8	Copper	0.3 - 0.7	$0.2 \text{ mg/m}^3$	$0.20 \text{ mg/m}^3$	N/e
7440-31-5	Tin	91 - 97	$2.00 \text{ mg/m}^3$	$2.00 \text{ mg/m}^3$	N/e
7440-22-4	Silver	2.7 - 4.2	$0.10 \text{ mg/m}^3$	$0.10 \text{ mg/m}^3$	N/e

#### **Section 3: Hazards Identification**

WHMIS Codes: n/a

NFPA Ratings: Health 1 Flammability 0 Reactivity 0 HMIS Ratings: Health 1 Flammability 0 Reactivity 0

**Eyes:** Fumes may cause eye irritation.

**Skin:** Fumes may cause skin irritation.

Inhalation: Inhalation of the fumes from this or other soldering products may cause headache, nausea, and

muscular pain.

**Ingestion:** Ingestion of the fumes from this or other soldering products may cause headache, nausea, and

muscular pain.

Chronic: Prolonged or repeated exposure due to ingestion may cause anemia, insomnia, weakness,

constipation and abdominal pain.

#### **Section 4: First Aid Measure**

**Eyes:** MOLTEN PRODUCT: Cool burns with plenty of low-pressure water. Get immediate medical attention.

SOLID PRODUCT: Remove any contact lenses. Immediately flush eyes with large quantities of water

for at least 15 minutes. Get medical attention if irritation develops.

**Skin:** MOLTEN PRODUCT: Immediately cool skin burns with water and cold packs for at least 15 minutes.

Do not put ice directly on the skin. Do not attempt to remove solidified product from the skin, as damage may result. Get immediate medical attention. SOLID PRODUCT: Immediately wash skin with soap and copious amounts of water. Use lotion to prevent dryness. Get medical attention if irritation

develops.

Inhalation: If symptoms of overexposure are experienced, evacuate to fresh air. If symptoms persist, seek

medical attention.

Ingestion: If person is conscious, immediately give 2 glasses of water. Do not induce vomiting. Get immediate

medical attention.



### **Section 5: Fire Fighting Measures**

Autoignition Temperature: N/a Flash Point: N/a LEL / UEL: N/e

Extinguishing Media: Alcohol foam, carbon dioxide, or dry chemical

**General Information:** Closed containers may explode when exposed to fire conditions.

### **Section 6: Accidental Release Measures**

**Spill Procedure:** If the material is in its solid state, pick up and reuse. When molten, allow to solidify, and the reuse if it is not contaminated. If contaminated, refer to section 13 for disposal information.

### Section 7: Handling and Storage

**Handling:** Wash thoroughly after handling. Avoid contact with eyes, skin, and clothing. Do not ingest or inhale. Do

not expose container to heat or flame.

Storage: Keep away from sources of ignition. Store in a cool, dry, well-ventilated area, away from incompatible

substances.

#### Section 8: Exposure Controls

Routes of entry: Eyes, ingestion, inhalation, and skin.

Ventilation: Use adequate general or local exhaust ventilation to keep airborne concentrations below exposure

limits

**Personal** Wear appropriate protective eyeglasses or chemical safety goggles. Wear appropriate protective

**Protection:** clothing to prevent skin contact. Use a NIOSH approved respirator when necessary.

### **Section 9: Physical and Chemical Properties**

**Physical** Solid **Odor:** None **Solubility:** Partially **Evaporation** N/e

State: Rate:

Boiling 1380°C Specific 5.9 - Vapor 1mmHq Vapor Density: N/e pH: N/a

Point: Gravity: 7.0 Pressure: @866°C

#### Section 10: Stability and Reactivity

Stability:Stable under ordinary use and storage conditions.Incompatibilities:Strong acids and strong oxidizers should be avoidedPolymerization:Will not occur under normal use and storage conditions.Decomposition:May emit fumes of carbon monoxide and carbon dioxide.

#### **Section 11: Toxicological Information**

 Sensitization: (effects of repeated exposure)
 No

 Carcinogenicity: (risk of cancer)
 No

 Teratogenicity: (risk of malformation in an unborn fetus)
 No

 Reproductive Toxicity: (risk of sterility)
 No

 Mutangenicity: (risk of inheritable genetic effects)
 No

Lethal Exposure Concentrations: Ingestion (LD50): N/e Inhalation (LC50): N/e Skin (LD50): N/e

#### **Section 12: Ecological Information**

**General Information:** No information on ecological toxicity or biodegradability is available at this time.

**Environmental Impact Data:** (percentage by weight)

**CFC:** 0 **HFC:** 0 **Cl.Solv:** 0 **VOC:** 0 **HCFC:** 0 **ODP:** 0



### **Section 13: Disposal Information**

General Information: Dispose of this material, contaminated absorbent material and other contaminated materials in an approved waste disposal facility, according to all applicable Federal, Sate / Provincial, and Local regulations. Recovery and reuse, rather than disposal, should be the ultimate goal in handling efforts.

### **Section 14: Transportation Information**

#### **Ground:**

Non-regulated

Shipper must be trained and certified. Refer to IATA Dangerous Goods Regulations.

**UN Number:** None

UN Pack Group: Not applicable **UN Class:** Non Hazardous ICAO/IATA: Non Hazardous Shipping Name: Non Hazardous

Non-regulated

### Section 15: Regulatory Information

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations.

SARA (Superfund Amendments and Reauthorization Act of 1986, USA, 40 CFR 372.4)

Reportable ingredients: Silver CAS# 7440-22-4, Copper CAS# 7440-50-8

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed or exempt from listing.

CAA (Clean Air Act, USA)

This product does not contain any class 1-ozone depletors.

This product does not contain any class 2-ozone depletors.

This product does not contain any chemicals listed as hazardous air pollutants.

California Proposition 65 (Chemicals know to cause cancer or reproductive toxicity, May 1, 1997 revision, USA) When used for soldering and similar applications chemicals may be produced which are known to some states to cause birth defects or other reproductive harm.

#### **Health Canada**

Labeling and containers used in this product are listed in compliance with Consumer Chemicals and Container regulations.

#### **Environment Canada**

Chemicals in this product are listed on the Domestic Substances List in the Canadian Environmental Protection Act


This product does not contain any ozone depleting substances.

#### **Industry and Science Canada**

Labeling, product identity, net quantity declaration, minimum printing type size heights, and packaging of this product is in compliance with the Consumer Packaging and Labeling Act and Regulations. This product is not slack filled in accordance to chapter 4 prohibitions.

RoHS (The restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2004).

This product is RoHS compliant.





### **Section 16: Other Information**

**Definitions:** N/a = not applicable, n/e = not established

Disclaimer: This material safety data sheet is provided as an information resource only. M.G. Chemicals believes the

information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to verify its validity. The buyer assumes all responsibility of using and handling the product in accordance with federal, state, and local regulations.

**PAGE 4 / 4** MSDS Code: 4900