



PRODUCT INFORMATION

#S56

Black/Yellow Hazard Striped Tunnel Tape

Description

Adhesive is zone coated on edges of hand tearable and puncture resistant cloth backing creating a non-adhesive tunnel for wires, cables or cords to lay (pass) under. Removes easily from carpet and other surfaces without leaving a residue. Can be repositioned several times without loss of adhesion.

Features

- Hand tearable
- Strong puncture resistant
- Removable
- No cable cleanup
- Repositionable

Backing	PE Coated Cloth	PE Coated Cloth
Adhesive	Natural rubber	Natural rubber
Total Thickness	11.8 mils	.299 mm
Adhesion to Stainless Steel	29 oz/in	7.85 N25mm
Service Temperature Range	-31 to 176F	-31 to 176F
Color	Black/Yellow Hazard Stripe	

Application

Taping down wires and cables in convention centers, auditoriums and TV studios.

Patent #5 211 784; 5 206 070

To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

†Note: Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith.

Materials should be stored at 70°F (21°C) with 50% relative humidity.