

Screened Paired LSF

Low Capacitance Computer Cable

pro-POWER



RoHS
Compliant

Application:

24 AWG low capacitance cables with a high level of screening. Provides interference free, high speed data transmission suitable for RS485 applications.

Construction:

Conductor	: Stranded tinned copper conductor
Insulation	: PE (Polyethylene)
Screen	: Aluminium polyester foil
Drain Wire	: Tinned copper
Braid	: TCWB (Tinned Copper Wire Braid)
Sheath	: LSF (Low Smoke and Fume)

Characteristics:

Voltage Rating	: 300V
Temperature Rating	: Fixed : -20°C to +80°C
Core Identification	: Pair 1 : Blue/White & White/Blue
Sheath Colour	: Grey

Electrical Characteristics:

Part Number	Capacitance at 1kHz pF/m	Max. Resistance of Conductor at 20°C Ω/km
PP000891	41.9	94.1
PP000892		

Dimensions:

Part Number	No. of Pairs	AWG Size	Conductor Area CSA mm ²	No. of Max. Strands × Strand Size (mm)	Nominal Overall Diameter mm	Nominal Weight kg/km
PP000891	1	24	0.2	7 × 0.2	5.9	54
PP000892						

Part Number Table

Description	Reel Length (m)	Part Number
Screened Pair Cable, 1PR, 24AWG	100	PP000891
	500	PP000892

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

pro-POWER