



Main

Circuit breaker application	Distribution
Range of product	C60
Device short name	C60 UL489
Poles description	3P
Number of protected poles	3
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	C

Complementary

[In] rated current	20 A (25 °C)
[Ue] rated operational voltage	277 V AC
Magnetic tripping limit	7...10 x In
Breaking capacity	AIR 10 kA at 277 V AC conforming to UL 489 AIR 10 kA at 277 V AC conforming to CSA Icu 10 kA at 277 V AC conforming to IEC 60947-2
Control type	Toggle
Local signalling	Positive break indication
9 mm pitches	6
Height	141 mm
Width	54 mm
Depth	74.2 mm
Product weight	0.33 kg
Mechanical durability	20000 cycles
Electrical durability	10000 cycles
Connections - terminals	Cable 2 cable(s) 2.5...6 mm ²
Tightening torque	1.5 N.m

Environment

Standards	CSA C22.2 No 5-02 GB 14048.2 IEC 60947-2 UL 489
IP degree of protection	IP20 IP40
Tropicalisation	2
Relative humidity	95 % (55 °C)
Ambient air temperature for operation	-30...70 °C
Ambient air temperature for storage	-40...80 °C
RoHS EUR conformity date	0649
RoHS EUR status	Compliant

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.