

#### **RoHS 2 and REACH Statement**

R

None of the RoHS 2 restricted materials or REACH substances of very high concern are intentionally added in manufacturing this product. Ref: European Union Directive 2011/65/EU and Regulation (EC) No. 1907/2006/CE. See Desco Limited Warranty at <u>Desco.com</u>.

А

"All personnel shall be bonded or electrically connected to the grounding / equipotential bonding system when handling ESDS [ESD sensitive] items. ...For standing operations, personnel shall be grounded via a wrist strap or by a footwear/flooring system." [ANSI/ESD S20.20 section 8.2 Personnel Grounding]

"If the contact area between the bottom of the foot and the floor is not continuous, charge generation may occur; especially when a person is walking. Heel straps must be worn on both feet to minimize the amount of time that the body of the person is isolated from ground while walking." [ESD Handbook ESD TR20.20 section 5.2.3 Flooring-Footwear System]

#### \*Patent US008189318B2

Unless otherwise noted, tolerance +/- 10%

Specifications and procedures subject to change without notice.



# Description

stat-A-REST™ Foot Grounders provide contact with ESD flooring providing a more continuous and reliable path-to-ground

to remove electrostatic charges. stat-A-REST<sup>™</sup> are easier to install than most foot grounders, designed to be used on standard shoes placing the grounding tab in the shoe under the foot. It is a suitable ESD footwear component in a Footwear / Flooring System meeting the ANSI/ESD S20.20 required limits < 1 x 10<sup>9</sup> ohms (footwear) per ESD SP9.2 and ESD TR53 and Footwear / Flooring requirements of < 3.5 x 10<sup>7</sup> ohms per

ANSI/ESD STM97.1 and < 100 volts per ANSI/ESD STM97.2.

## Components

- A. Non-Marring Thermoplastic Elastomer (TPE)
- B. 30 Inch Conductive 8-Strand Nylon Polyester Grounding Tab
- C. Size molded on bottom of unit

## **Electrical Properties**

PropertyTest MethodPoint to GroundableANSI/ESD STPoint Resistance:ANSI/ESD ST

Test Method ANSI/ESD STM97.1, ESD SP9.2, ESD TR53 Value < 1 x 10<sup>9</sup> ohms

See independent test lab report here.

### **Specifications**

Yellow	<u>04564</u>	<u>04565</u>	<u>04566</u>	<u>04567</u>
Blue	<u>04597</u>	<u>04594</u>	<u>04595</u>	<u>04596</u>
Size	Small	Medium	Large	XLarge
Length	9.5"	10.25"	11"	11.75"
Width	3.25"	3.75"	4.375"	4.625"
Shoe Size Women	5-8	8.5-10.5	11-13.5	13.5+
Shoe Size Men	4-6	6.5-8.5	9-12	12.5-14.5
Shoe Size EU	35-38	39-43	44-46	46-48

Sold in pairs

# stat-A-REST™ Foot Grounders DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com DRAWING DATE: PHONE (909) 627-8178 DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 DMMBER June PHONE (781) 821-8370 04594 2015

© 2015 DESCO INDUSTRIES INC. Employee Owned



Made in the United States of America