



- Ground cord used to connect mats to (Earth Bonding Point) plugs
- 1 megohm (1×10^6 ohms) resistor in socket end
- 2.5mm cord diameter
- Several lengths available
- PVC insulation with 7 ends duplex tinsel copper conductor

| Item # | Description |
|-----------|---|
| VER-26968 | CORD,STRAIGHT,1.5M,10MMSOCKET/ M5 RING TERMINAL |

"EPA ground cords shall be used to make electrical connections between groundable points and the EPA ground facility.

Where a single resistor is used in the EPA ground cord, this shall be located near the groundable point. Where more than one resistor is used, a resistor of a minimum resistance value of one half the total resistance shall be located near the groundable point.

When accessible, the EPA ground cord and its groundable point connection shall be shrouded by insulating material." (EN 61340-5-1 section 5.3.4 EPA ground cords)

Unless otherwise noted, tolerance is $\pm 10\%$
Specifications and procedures subject to change without notice.



Vermason

Straight Cord, 10mm Socket, M5 Ring Terminal

VERMASON
UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH,
HERTS, SG6 2TD UK
PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440
E-MAIL: Service@Vermason.co.uk, INTERNET: Vermason.co.uk

Drawing Number
VER-26968

DATE:
September
2015