

### Features and Benefits

The PowerCat 1 Port Shuttered Fixed Wallplate offers an economic alternative to the modular system, eliminating the need for separate components as only one part is needed. The Wallplate is a complete assembly, comprising 1, C5E RJLP Connectors, Fascia, Spring Loaded Shutters and a protected labelling facility. The product is designed to be compatible with UK single gang back boxes.

Molex Premise Networks unique patented RJLP RJ45 Connector is engineered to meet the highest performance standards in the industry and offers a low profile, space saving design, that allows installation in shallow back boxes and trunking.

Suitable for high speed data transmission, the PowerCat RJLP RJ45 was designed to meet the requirements of the C5E standard which demands compliance with the PowerSum principle of measurement and test.

- UK standard 86 x 86mm fascia
- Low profile C5E RJ45 Connector
- Spring loaded shutters
- FTP version provides through-shield continuity

### Technical Specification

#### Termination Tools:

Molex and industry standard tooling

#### IDC Terminations:

Suitable for 0.4mm - 0.6mm solid or stranded cable, maximum o.d. 1.5mm. Two wires may be terminated for daisy-chain applications.

Patents pending on connector and module designs.

#### Mechanical

##### Jack Connector

Operating Life: Minimum 500 insertion cycles  
 Contact Material: Phosphor Bronze  
 Contact Plating: 1.25 micrometers Au/Ni  
 Material: UL 94V0 Thermoplastic

##### IDC Connector

Operating Life: Minimum 100 Reterminations  
 Contact Material: Phosphor Bronze  
 Contact Plating: Sn/Pb over Ni  
 Wire Size: 2x26-22 awg solid or stranded

#### Electrical

D.C. Resistance: <20mΩ  
 D.C. Resistance Imbalance: <2.0mΩ  
 Insulation Resistance: > 100mΩ  
 Attenuation (dB) @1MHz 0.0121  
                                   @16MHz 0.0193  
                                   @100MHz 0.1052  
 Crosstalk (dB) @1MHz -84.26  
                                   @16MHz -60.03  
                                   @100MHz -45.70  
 PowerSum Worst Pair(dB) @100MHz -41.83  
 Return Loss (dB) @1MHz -65.0  
                                   @16MHz -48.0  
                                   @100MHz - 30.0



## ORDERING INFORMATION

Order No.	SAP No.	Description
WNC-00007-02	Consult Molex	1 Port PowerCat Fixed Shuttered UTP Wallplate 568B Cat 5E, White
WNC-00010-02	Consult Molex	1 Port PowerCat Fixed Shuttered FTP Wallplate 568B Cat 5E, White

### MOLEX PREMISE NETWORKS

**Americas**  
 Tel: 630 969 4550  
 www.molexpn.com

**EMEA**  
 Tel: 44 (0)2392 205800  
 www.molexpn.co.uk

**APAC**  
 Tel: 61 3 9971 7111  
 www.molexpn.com.au