Defence Standard 61-12 Part 4 - 7-2-A Unscreened Multicore Cable





RoHS Compliant

position)

Specifications:

Conductor Material Conductor Area CSA Construction Stranded Dia.(mm) Insulation Thickness Insulation Dia.(+/-0.1mm) Insulation Insulation Insulation Colours Jacket Material Jacket Colour Nylon Rip Cord : Tinned Copper : 0.22mm² : T0.2± 0.008×7 : 0.58 : 0.31 : 1.2 : PVC : See Insulation Colours Table : PVC : Black : 150D

Electrical Characteristics:

	<u></u>
Max.Conductor DC Resistance at 20°C (Ω /Km)	: <93.8
20°C Insulation Resistance (MΩ/Km)	: >200
Max. Conductor Temperature	: +70°C
Min. Ambient Temperature	: -55°C (After installation and only when cable is in a fixed p
Rated Voltage(V)	: 440

Insulation Colours table

Core Number	Colour	Core Number	Colour	Core Number	Colour
1	Red	13	Red/Blue	25	Yellow/Green
2	Blue	14	Green/Red	26	White/Green
3	Green	15	Yellow/Red	27	Green/Black
4	Yellow	16	White/Red	28	Orange/Green
5	White	17	Red/Black	29	Grey/Green
6	Black	18	Red/Brown	30	Yellow/Brown
7	Brown	19	Yellow/Blue	31	White/Brown
8	Violet	20	White/Blue	32	Brown/Black
9	Orange	21	Blue/Black	33	Grey/Brown
10	Pink	22	Orange/Blue	34	Yellow/Violet
11	Turquoise	23	Green/Blue	35	Violet/Black
12	Grey	24	Grey/Blue	36	White/Violet

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk





Part Number Table

Description	Core No.	Jacket Diameter (mm)	Filler	Reel Length (m)	Part Number
Cable, Unscreened, DEF 7-2-2A	2	3.4	-	25	PP000272
				100	PP000273
Cable, Unscreened, DEF 7-2-3A	3	3.6		25	PP000274
				100	PP000275
Cable, Unscreened, DEF 7-2-4A	4	3.9		25	PP000276
				100	PP000277
Cable, Unscreened, DEF 7-2-6A	6	4.6	1.2 PVC Strip	25	PP000278
				100	PP000279
Cable, Unscreened, DEF 7-2-8A	8	5.6	1.9PVC Strip	25	PP000280
				100	PP000281
Cable, Unscreened, DEF 7-2-12A	12	6.1	-	25	PP000282
				100	PP000283
Cable, Unscreened, DEF 7-2-18A	18	7.4	1.2PVC Strip	25	PP000284
				100	PP000285
Cable Unserversed DEE 7.2.204	20	7.8	-	25	PP000286
Cable, Unscreened, DEF 7-2-20A				100	PP000287
Cable, Unscreened, DEF 7-2-25A	25	8.7		25	PP000288
				100	PP000289
Cable, Unscreened, DEF 7-2-36A	36	9.8	1.2PVC Strip	100	PP000290

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

