

Features

Regulated Converters

- 2:1 Wide Input Range
- 2kVDC/1 Second Isolation
- -40°C to +75°C Operating Temperature @ Full Load
- Industry Standard Pinout (SIP8)
- EN/UL62368, UL60950, CB Report (pending)
- Low Cost

Description

The RSE is a low cost isolated, regulated and short-circuit protected DC/DC converter designed for industrial applications. A compact SIP8 case size, 2:1 input, 2kVDC isolation and a wide operating temperature range of -40°C to +75°C without derating makes the RSE series ideal for industrial, transport and general-purpose on-board 5V power supplies. Industrial Class A EMC levels can be met with a simple Pi-filter and the converters come with a three year warranty.

Selection Guide

Part Number	nom. Input Voltage [VDC]	Input Current @ full load [mA]	Output Voltage [VDC]	Output Current [mA]	Efficiency typ. ⁽¹⁾ [%]	max. Capacitive Load ⁽²⁾ [µF]
RSE-0505S/H2	4.5 - 9	526	5	400	76	6800
RSE-2405S/H2	18 - 36	103	5	400	80	6800

Notes:

Note1: Efficiency is tested by nominal input and full load at +25°C ambient.

Note2: Max. cap load is tested by nominal input and full resistive load.

Specifications (measured @ ta= 25°C, nominal Vin, full load unless otherwise specified)

BASIC CHARACTERISTICS					
Parameter	Condition		Min.	Typ.	Max.
Internal Input Filter			Capacitor		
Input Voltage Range	nom. Vin=	5VDC 24VDC	4.5VDC 18VDC	5VDC 24VDC	9VDC 36VDC
Maximum Reverse Voltage					0VDC
Input Surge Voltage	100ms max	nom. Vin=	5VDC 24VDC	15VDC 50VDC	
Quiescent Current	nom. Vin=		5VDC 24VDC	40mA 3mA	
Start-up time				500µs	
Rise time				450µs	
Hold-up time				10µs	
Internal Operating Frequency			130kHz		
Minimum Load				0%	
Output Ripple and Noise ⁽³⁾	20MHz BW, 0-100% load				75mVp-p
ON/OFF CTRL ⁽⁴⁾	DC-DC ON DC-DC OFF		Open or 0V < Vr < 0.8VDC 2V < Vr < 6VDC		
Input Current of CTRL Pin	5V VCTRL 3.3V VCTRL			15mA 10mA	
Standby Current				0.75mA	1.5mA

Notes:

Note3: Measurements are made with a 0.1µF MLCC across output (low ESR).


Note4: Please refer to „Application and Installation“ for CTRL pin circuit.

continued on next page

RECOM
DC/DC Converter


RSE

2 Watt
SIP8
Single Output




EN55022 Compliant
EN62368-1 (pending)
UL62368 (pending)
UL60950-1 (pending)
CB Report (pending)

Specifications (measured @ $t_a = 25^\circ\text{C}$, nominal V_{in} , full load unless otherwise specified)



REGULATIONS

Parameter	Condition	Value
Output Accuracy	0-100% load	$\pm 2.0\%$ max.
Line Regulation	low line to high line, full load	$\pm 0.2\%$ max.
Load Regulation	0% to 100% load	$\pm 0.5\%$ max.




PROTECTIONS

Parameter	Type	Value
Short Circuit Protection (SCP)	below $100\text{m}\Omega$	continuous, auto recovery
Isolation Voltage	I/P to O/P	tested for 1s
Isolation Resistance		$1\text{G}\Omega$ min.
Isolation Capacitance		100pF max.
Insulation Grade		functional

continued on next page

Specifications (measured @ $t_a = 25^\circ\text{C}$, nominal V_{in} , full load unless otherwise specified)

Surge Protection Circuit according to EN61000-4-5, Criteria A



nom. V_{in}	TVS	C1
5VDC	P4SMAJ11A	N/A
24VDC	P4SMAJ36A	220 $\mu\text{F}/100\text{V}$

Notes:


Note5: An input fuse is required if the mains supply is not over-current protected. Recommended fuse: T2A slow blow type.

ENVIRONMENTAL

Parameter	Condition	Value
Operating Temperature Range	without derating (see graph)	-40°C to +75°C
Maximum Case Temperature		105°C
Temperature Coefficient		$\pm 0.05\%/^\circ\text{C}$
Operating Altitude		2000m
Operating Humidity	non-condensing	5% - 95% RH max.
Pollution Degree		PD3
MTBF	according to MIL-HDBK-217F, G.B.	+25°C 781 x 10 ³ hours +75°C 2289 x 10 ³ hours
Vibration		MIL-STD 202G

Derating Graph

(@ Chamber and natural convection 0.1 m/s)



SAFETY AND CERTIFICATIONS


Certificate Type (Safety)	Report / File Number	Standard
Audio/video, information and communication technology equipment - Safety requirements (LVD)	pending	EN62368-1
Audio/video, information and communication technology equipment - Safety requirements (CB Scheme)	pending	UL62368-1
Information Technology Equipment, General Requirements for Safety (LVD)	pending	UL60950-1
RoHS2+		RoHS-2011/65/EU + AM2 (10/10)

continued on next page

Specifications (measured @ $t_a = 25^\circ\text{C}$, nominal V_{in} , full load unless otherwise specified)


EMC Compliance	Condition	Standard / Criterion
Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement	see filter suggestions	EN55022, Class A/B
ESD Electrostatic discharge immunity test	Air: $\pm 8\text{kV}$; Contact: $\pm 4\text{kV}$	EN61000-4-2, Criteria A
Radiated, radio-frequency, electromagnetic field immunity test		EN61000-4-3
Fast Transient and Burst Immunity	$\pm 1\text{kV}$	EN61000-4-4, Criteria A
Surge Immunity	$\pm 1\text{kV}$	EN61000-4-5, Criteria A
Immunity to conducted disturbances, induced by radio-frequency fields		EN61000-4-6

EMC Filtering Suggestions for EN55022 Class A



nom. V_{in}	C1	C2	L1
5VDC	22 μF /50V MLCC	22 μF /50V MLCC	3 μH Choke
24VDC			

EMC Filtering Suggestions for EN55022 Class B





nom. V_{in}	C1	C2	C3	L1
5VDC	22 μF /50V MLCC	22 μF /50V MLCC	1000pF/3kV	0.45mH CMC
24VDC				

DIMENSION and PHYSICAL CHARACTERISTICS		
Parameter	Type	Value
Material	Case	non-conductive black plastic, (UL94V-0)
	Potting	epoxy, (UL94V-0)
	PCB	FR4, (UL94V-0)
Package Dimension (LxWxH)		21.8 x 9.2 x 11.1mm
Package Weight		4.7g

continued on next page

Specifications (measured @ $t_a = 25^\circ\text{C}$, nominal V_{in} , full load unless otherwise specified)

Dimension Drawing (mm)



Pin Connection

Pin #	Single
1	-Vin
2	+Vin
3	CTRL
5	NC
6	+Vout
7	-Vout
8	NC

NC= no connection


Tolerance: xx.x= $\pm 0.5\text{mm}$

xx.xx= $\pm 0.25\text{mm}$

Pin dimension: $\pm 0.1\text{mm}$

INSTALLATION and APPLICATION

ON/OFF CTRL Circuit



DC-DC ON: Open or $0V < V_r < 0.8V_{DC}$

DC-DC OFF: $2V < V_r < 6V$

PACKAGING INFORMATION

Packaging Dimension (LxWxH)	tube	520.0 x 11.2 x 18.2mm
Packaging Quantity		22pcs
Storage Temperature Range		-55°C to +125°C
Storage Humidity		5% - 95% RH max.

The product information and specifications are subject to change without prior notice. RECOM products are not authorized for use in safety-critical applications (such as life support) without RECOM's explicit written consent. A safety-critical application is defined as an application where a failure of a RECOM product may reasonably be expected to endanger or cause loss of life, inflict bodily harm or damage property. The buyer shall indemnify and hold harmless RECOM, its affiliated companies and its representatives against any damage claims in connection with the unauthorized use of RECOM products in such safety-critical applications.