## **Product datasheet** Characteristics

# NSYCAG12LPH1

Watertight condensationless valves IP68 ØM12 F16 litres/hour when 0,07 bar



#### Main

Man				
Range	ClimaSys CA			
Range	ClimaSys			
Accessory / separate part type	Sealed anti-condensation valve			
Product compatibility	All enclosures			
Fixing mode	Screwed			
Device composition	1 x valve			
Quantity per set	Set of 10			

#### Complementary

· · ·   - · · · · · · · · · · · · ·				
Material	PA6			
	Acrilic co-polymer ( membrane )			
Diameter	10.2 mm			
Flame retardance	V2			
Operating temperature	-40150 °C			
Permeability	16 l/h			
Pressure setting range	< 1 bar			

### Offer Sustainability

Main					
Range	ClimaSys CA				
Range	ClimaSys				
Accessory / separate part type	Sealed anti-condensation valve				
Product compatibility	All enclosures				
Fixing mode	Screwed				
Device composition	1 x valve				
Quantity per set	Set of 10				
Complementary					
Material	PA6				
	Acrilic co-polymer ( membrane )				
Diameter	10.2 mm				
Flame retardance	V2				
Operating temperature	-40150 °C				
Permeability	16 l/h				
Pressure setting range	< 1 bar				
Offer Sustainability					
Sustainable offer status	Not Green Premium product				
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity				
	Schneider Electric declaration of conformity				
REACh	Reference not containing SVHC above the threshold				
	Reference not containing SVHC above the threshold				
Contractual warranty					
Warranty period	18 months				

#### Contractual warranty

	•			
Warranty period		18 months		

Life Is On Schneider

1