
KEMET Part Number: R75LF24704000K

(75LF24704000K)



Film, Metallized Polypropylene, Commercial Grade, R75L, 0.047 uF, 10%, 560 V, 85C, Lead Spacing = 10mm



| Dimensions | | |
|------------|-----------------|--|
| L | 13mm +0.3mm | |
| Н | 11mm +0.1mm | |
| Т | 5mm +0.2mm | |
| S | 10mm +/-0.4mm | |
| LL | 30mm +5mm | |
| F | 0.8mm +/-0.05mm | |

| Packaging Specifications | | |
|--------------------------|-----------|--|
| Packaging: | Bulk, Bag | |

| General Information | | |
|---------------------|--------------------------|--|
| Dielectric: | Metallized Polypropylene | |
| Style: | Radial | |
| Series: | R75L | |
| Features: | Pulse | |
| RoHS: | Yes | |
| Lead: | Wire Leads | |

| Specifications | | |
|------------------------|----------------------------------|--|
| Capacitance: | 0.047 uF | |
| Capacitance Tolerance: | 10% | |
| Voltage DC: | 560 VDC, 336 VDC (105C) | |
| Voltage AC: | 250 VAC | |
| Temperature Range: | -55/+105C | |
| Rated Temperature: | 85C | |
| Dissipation Factor: | 4% 1kHz, 6% 10kHz, 25% 100kHz | |
| Insulation Resistance: | 640 GOhms | |
| Max dVdt: | 1,500 V | |
| Inductance: | 10 nH | |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

