Solid State Relay



RoHS Compliant



Description

The product is single channel din-rail mounted module with 5A. Control voltage is 15-32V DC and isolation voltage is 4000V ACrms with high EMC capability, high inrush current, special for automatic machinery, control system, elevator, entertainment equipment.

Features

- · Load Current: 0.1A to 5A
- · Din Rail Mounted
- DC Control
- LED Indication
- High EMC Capability
- High Inrush Current

Application

Suitable for Automatic Equipment, Control System, Entertainment Equipment.

Technical Specification

Input Circuit

Control Voltage Range : 15V DC to 32V DC

Min. Turn-On Voltage: 15V DCMin. Turn-Off Voltage: 1V DCMax. Input Current: 25mA

Output Circuit

Load Voltage Range : 48V AC to 280V AC

Transient Overvoltage : 600Vpk
Load Current Range : 0.1A to 5A

Max. Turn-On Time : 1/2AC Cycle + 1ms

Max. Surge Current (@10 ms) : 60A

Max. Off-State Leakage Current [@ Rated Voltage] : 5mA

Max. On-State Voltage Drop [@ Rated Current] : 1.5Vrms

Min. Off-State dv/dt [@ Max. Rated Voltage] : 200V/µs

General Information

 Dielectric Strength Input/Output
 : ≥4000Vrms

 Ambient Operating Temperature Range
 : -30°C to +80°C

 Ambient Storage Temperature Range
 : -30°C to +100°C

Weight (Typical) : 55g


www.element14.com www.farnell.com www.newark.com



Solid State Relay




Diagram




Dimensions: Millimetres

Wiring Diagram




Thermal Curve



Ambient Temperature ($^{\circ}$ C)

Part Number Explanation



Part Number Table

Description	Part Number
Solid State Relay, Din module, 280V AC, 5A, 15-32V DC	MCDRA-1/KSD240D5-H(037)

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com www.farnell.com www.newark.com



20/06/17 V1.0