

Aluminum Electrolytic, 85C, ALS60, 680 uF, 20%, 550 V, -40/+85C



General Information	
Dielectric:	Aluminum Electrolytic
Series:	ALS60
Description:	High Voltage, Screw Terminal, Aluminum Electrolytic
Features:	High Voltage
RoHS:	Yes
Notes:	Dimensions D And L Include Slewing. MS (MxH) = M12x16

Dimensions	
D	51mm +/-1mm
L	105mm +/-2mm
T	5.5mm +/-0.5mm
S	22.2mm +/-0.5mm
DT	13mm +/-0.5mm
LT	110.5mm +/-1mm
TD	10mm MIN
V	13.7mm NOM
Z	10mm NOM

Specifications	
Capacitance:	680 uF
Capacitance Tolerance:	20%
Voltage DC:	550 VDC, 605 VDC (Surge)
Temperature Range:	-40/+85C
Rated Temperature:	85C
Life:	18000 Hrs
Resistance:	441.15 mOhms (100Hz 20C), 390.9 mOhms (10kHz 20C)
Current:	4.9 Amps (100Hz 85C), 8.08 Amps (10kHz 85C)
Leakage Current:	2244 uAmps (5min 20C)

Packaging Specifications	
Weight:	300 g
Slewing:	Yes
Packaging:	Bulk