
KEMET Part Number: C1210C335K3NACTU

(C1210C335K3NAC7800)



Ceramic, 150C-(CxxxxC), 3.3 uF, 10%, 25 V, 1210, X8L, SMD, MLCC, High Temperature, Temperature Stable



Dimensions		
L	3.2mm +/-0.2mm	
W	2.5mm +/-0.2mm	
Т	1.7mm +/-0.20mm	
В	0.5mm +/-0.25mm	

Packaging Specifications		
Packaging:	T&R, 180mm, Plastic Tape	
Packaging Quantity:	2000	

General Information		
Style:	SMD Chip	
Series:	150C-(CxxxxC)	
Chip Size:	1210	
Description:	SMD, MLCC, High Temperature, Temperature Stable	
Features:	High Temperature, Temperature Stable	
RoHS:	Yes	
Termination:	Tin	
Marking:	No	
Failure Rate:	N/A	
Miscellaneous:	Note: Referee time for X8L dielectric for this part number is 1000 hours	

Specifications		
Capacitance:	3.3 uF	
Capacitance Tolerance:	10%	
Voltage DC:	25 VDC	
Dielectric Withstanding Voltage:	62.5 V	
Temperature Range:	-55/+150C	
Temperature Coefficient:	X8L	
Dissipation Factor:	2.5%	
Aging Rate:	3% Loss/Decade Hour	
Insulation Resistance:	152 MOhms	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

