
KEMET Part Number: PHE850EA4220MA01R17

(F850AG222M300A)



Film, Metallized Polypropylene, Safety, PHE850/F850, 2200 pF, 20%, 1,250 V, 300 V, 110C, Lead Spacing = 10mm



Dimensions		
L	13mm MAX	
Н	9mm MAX	
Т	4mm MAX	
S	10mm +/-0.4mm	
LL	17mm NOM	
F	0.6mm NOM	

Packaging Specifications	
Packaging:	Bulk
Packaging Quantity:	1000

General Information		
Dielectric:	Metallized Polypropylene	
Style:	Radial	
Series:	PHE850/F850	
Features:	Pulse	
RoHS:	Yes	
Lead:	Wire Leads	
Approvals:	ENEC, UL, cUL	
Miscellaneous:	Not For New Design, Please Check Possible Alternative Parts (AltPart)	

Specifications		
Capacitance:	2200 pF	
Capacitance Tolerance:	20%	
Voltage DC:	1250 VDC	
Voltage AC:	300 VAC	
Temperature Range:	-55/+110C	
Rated Temperature:	110C	
Dissipation Factor:	0.15% 1kHz, 0.2% 10kHz, 0.6% 100kHz	
Insulation Resistance:	30 GOhms	
Max dVdt:	100 V	
Safety Class:	Y2	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

