

**KEMET Part Number: C0402C472K4RACTU**  
(C0402C472K4RAC7867)

Ceramic, SMD Comm X7R, 4700 pF, 10%, 16 V, 0402, X7R, SMD, MLCC, Temperature Stable, Class II



| Dimensions |                 |
|------------|-----------------|
| L          | 1mm +/-0.05mm   |
| W          | 0.5mm +/-0.05mm |
| T          | 0.5mm +/-0.05mm |
| S          | 0.3mm MIN       |
| B          | 0.3mm +/-0.1mm  |

| Packaging Specifications |                        |
|--------------------------|------------------------|
| Packaging:               | T&R, 180mm, Paper Tape |
| Packaging Quantity:      | 10000                  |

| General Information |  |
|---------------------|--|
| Style:              | SMD Chip   |
| Series:             | SMD Comm X7R   |
| Chip Size:          | 0402   |
| Description:        | SMD, MLCC, Temperature Stable, Class II                                  |
| Features:           | Temperature Stable, Class II   |
| RoHS:               | Yes  |
| Termination:        | Tin  |
| Marking:            | No   |
| Failure Rate:       | N/A  |
| Miscellaneous:      | Note: Referee time for X7R dielectric for this part number is 1000 hours |

| Specifications                   |                     |
|----------------------------------|---------------------|
| Capacitance:                     | 4700 pF             |
| Capacitance Tolerance:           | 10%                 |
| Voltage DC:                      | 16 VDC              |
| Dielectric Withstanding Voltage: | 40 V                |
| Temperature Range:               | -55/+125C           |
| Temperature Coefficient:         | X7R                 |
| Dissipation Factor:              | 3.5% 1kHz 25C       |
| Aging Rate:                      | 3% Loss/Decade Hour |
| Insulation Resistance:           | 100 GOhms           |