Product datasheet Characteristics

LA1KN04 TeSys K - Auxiliary contact block - 4 NC - screwclamps terminals



Main

TTO IT	
Range of product	TeSys K TeSys K control relay
Range	TeSys
Device short name	LA1
Product or component type	Auxiliary contact block
Auxiliary contacts operation	Instantaneous
Pole contact composition	4 NC
Connections - terminals	Screw clamp terminals 1 cable 0.341.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 0.341.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 0.754 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable 0.754 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 1.54 mm ² - cable stiffness: solid Screw clamp terminals 1 cable 1.54 mm ² - cable stiffness: solid

Complementary

4.1.	
Main	
Range of product	TeSys K TeSys K control relay
Range	TeSys
Device short name	LA1
Product or component type	Auxiliary contact block
Auxiliary contacts operation	Instantaneous
Pole contact composition	4 NC
Connections - terminals	Screw clamp terminals 1 cable 0.341.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 0.341.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 0.754 mm ² - cable stiffness: flexible - without cable end
	Screw clamp terminals 2 cable 0.754 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 1.54 mm ² - cable stiffness: solid Screw clamp terminals 2 cable 1.54 mm ² - cable stiffness: solid
	Screw clamp terminals 2 cable 0.754 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 1.54 mm ² - cable stiffness: solid Screw clamp terminals 2 cable 1.54 mm ² - cable stiffness: solid
Complementary Mounting location	Screw clamp terminals 2 cable 0.754 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 1.54 mm ² - cable stiffness: solid Screw clamp terminals 2 cable 1.54 mm ² - cable stiffness: solid Front
	Screw clamp terminals 2 cable 0.754 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 1.54 mm ² - cable stiffness: solid Screw clamp terminals 2 cable 1.54 mm ² - cable stiffness: solid
Mounting location	Screw clamp terminals 2 cable 0.754 mm² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 1.54 mm² - cable stiffness: solid Screw clamp terminals 2 cable 1.54 mm² - cable stiffness: solid Front 600 V - for control circuit - conforming to CSA C22.2 690 V - for control circuit - conforming to BS 5424 690 V - for control circuit - conforming to IEC 60947
Mounting location [Ui] rated insulation voltage [Ue] rated operational voltage [Ith] conventional free air thermal	Screw clamp terminals 2 cable 0.754 mm² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 1.54 mm² - cable stiffness: solid Screw clamp terminals 2 cable 1.54 mm² - cable stiffness: solid Front 600 V - for control circuit - conforming to CSA C22.2 690 V - for control circuit - conforming to BS 5424 690 V - for control circuit - conforming to IEC 60947 750 V - for control circuit - conforming to VDE 0010 group C
Mounting location [Ui] rated insulation voltage [Ue] rated operational voltage [Ith] conventional free air thermal current	Screw clamp terminals 2 cable 0.754 mm² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 1.54 mm² - cable stiffness: solid Screw clamp terminals 2 cable 1.54 mm² - cable stiffness: solid Front 600 V - for control circuit - conforming to CSA C22.2 690 V - for control circuit - conforming to BS 5424 690 V - for control circuit - conforming to IEC 60947 750 V - for control circuit - conforming to VDE 0010 group C <= 690 V AC <= 400 Hz
Mounting location [Ui] rated insulation voltage [Ue] rated operational voltage [Ith] conventional free air thermal current Irms rated making capacity	Screw clamp terminals 2 cable 0.754 mm² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 1.54 mm² - cable stiffness: solid Screw clamp terminals 2 cable 1.54 mm² - cable stiffness: solid Front 600 V - for control circuit - conforming to CSA C22.2 690 V - for control circuit - conforming to BS 5424 690 V - for control circuit - conforming to IEC 60947 750 V - for control circuit - conforming to VDE 0010 group C <= 690 V AC <= 400 Hz
Mounting location [Ui] rated insulation voltage [Ue] rated operational voltage [Ith] conventional free air thermal current Irms rated making capacity Permissible short-time rating	Screw clamp terminals 2 cable 0.754 mm² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 1.54 mm² - cable stiffness: solid Screw clamp terminals 2 cable 1.54 mm² - cable stiffness: solid Front 600 V - for control circuit - conforming to CSA C22.2 690 V - for control circuit - conforming to BS 5424 690 V - for control circuit - conforming to IEC 60947 750 V - for control circuit - conforming to VDE 0010 group C <= 690 V AC <= 400 Hz
Mounting location	Screw clamp terminals 2 cable 0.754 mm² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 1.54 mm² - cable stiffness: solid Screw clamp terminals 2 cable 1.54 mm² - cable stiffness: solid Front 600 V - for control circuit - conforming to CSA C22.2 690 V - for control circuit - conforming to BS 5424 690 V - for control circuit - conforming to IEC 60947 750 V - for control circuit - conforming to VDE 0010 group C <= 690 V AC <= 400 Hz



Non overlap distance	0.5 mm
Insulation resistance	> 10 MOhm for control circuit
Tightening torque	1.3 N.m - on screw clamp terminals - with screwdriver Philips No 2
Depth	35 mm
Product weight	0.045 kg

Environment

Environmental characteristic	Normal environment
Standards	VDE 0660 NF C 63-110 IEC 60947 BS 5424
Product certifications	CSA UL
IP degree of protection	IP2x conforming to VDE 0106
Protective treatment	TC conforming to IEC 60068
Ambient air temperature for operation	-2550 °C
Ambient air temperature for storage	-5080 °C
Operating altitude	2000 m without derating in temperature

18 months

Contractual warranty

Warranty period