



Main

Range	TeSys
Device short name	LA1SK
Product or component type	Auxiliary contact block
Product compatibility	LC1SK
Auxiliary contacts operation	Instantaneous
Pole contact composition	1 NO + 1 NC
Connections - terminals	Screw clamp terminals 2 cable 1.5...4 mm ² - cable stiffness: solid Screw clamp terminals 1 cable 1.5...6 mm ² - cable stiffness: solid Screw clamp terminals 1 cable 0.5...6 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 0.35...2.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 0.35...6 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable 0.35...1.5 mm ² - cable stiffness: flexible - without cable end

Complementary

Mounting location	Front side
[Ui] rated insulation voltage	690 V - conforming to CSA C22.2 No 14 690 V - conforming to BS 5424 690 V - conforming to IEC 60947 690 V - conforming to VDE 0110 group C
[Ue] rated operational voltage	690 V AC <= 400 Hz
[Ith] conventional free air thermal current	10 A at <= 55 °C
Associated fuse rating	VDE 0660 IEC 60947
Tightening torque	0.8 N.m - on screw clamp terminals
Width	27 mm
Product weight	0.022 kg

Environment

Standards	IEC 60947 VDE 0660 NF C 63-110
-----------	--------------------------------------

BS 5424

Product certifications	CSA UL
IP degree of protection	IP2x
Protective treatment	TC conforming to IEC 60068
Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	-50...70 °C
Operating altitude	2000 m without derating in temperature

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0718 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------