



General Description:

NPN general purpose transistors in Surface-Mounted Device (SMD) plastic packages

Features:

- General-purpose transistors
- SMD plastic packages
- Two different gain selections
- High current gain
- Excellent h_{FE} linearity
- Low noise between 30Hz and 15kHz
- For AF input stages and driver applications

Applications:

General-purpose switching and amplification

Max. Ratings & Characteristics : $T_A = 25^\circ\text{C}$ unless otherwise specified

Parameter	Symbol	Value	Unit
Collector - Base Voltage	V_{CBO}	80	V
Collector - Emitter Voltage	V_{CEO}	65	V
Emitter - Base Voltage	V_{EBO}	6	V
Collector Current - Continuous	I_C	0.1	A
Collector Dissipation	P_C	250	mW
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	417	$^\circ\text{C}/\text{W}$
Junction and Storage Temperature	T_J, T_{STG}	-55 to +150	$^\circ\text{C}$

Max. Ratings & Characteristics : $T_A = 25^\circ\text{C}$ unless otherwise specified


Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Collector - Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = -10\mu\text{A}$ $I_E = 0$	80	-	-	V
Collector - Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = -10\text{mA}$ $I_B = 0$	65	-	-	V
Emitter - Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 10\mu\text{A}$ $I_C = 0$	6	-	-	V

Max. Ratings & Characteristics : $T_A = 25^\circ\text{C}$ unless otherwise specified (Cont.)

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Collector Base Cut-off Current	I_{CBO}	$V_{CB} = 30V, I_E = 0$ $V_{CB} = 30V, I_E = 0, T_J = 150^\circ\text{C}$	-	-	15 5	nA uA
Emitter Base Cut-off Current	I_{EBO}	$V_{EB} = -5V, I_C = 0$	-	-	100	μA
DC Current Gain BC846A BC846B	h_{FE}	$V_{CE} = 5V, I_C = -2\text{mA}$	-	90 150	-	-
DC Current Gain BC846 BC846A BC846B	h_{FE}	$V_{CE} = 5V, I_C = 10\mu\text{A}$	110 110 200	-	450 220 450	-
Collector - Emitter Saturation Voltage	$V_{CE(SAT)}$	$I_C = 10\text{mA}, I_B = 0.5\text{mA}$ $I_C = 10\text{mA}, I_B = 5\text{mA}$	-	0.09 0.2	0.25 0.6	V
Base - Emitter Saturation Voltage	$V_{BE(SAT)}$	$I_C = 10\text{mA}, I_B = 0.5\text{mA}$ $I_C = 100\text{mA}, I_B = 5\text{mA}$	-	0.7 0.9		V
Base Emitter Voltage	$V_{BE(ON)}$	$I_C = 2\text{mA}, V_{CE} = 5V$ $I_C = 10\text{mA}, V_{CE} = 5V$	0.58 -	0.66 -	0.7 0.77	V
Collector Capacitance	C_C	$V_{CB} = 10V, I_E = I_C = 0$ $f = 1\text{MHz}$	-	2.5	-	pF
Transition Frequency	F_T	$V_{CE} = -5V, I_C = 10\text{mA},$ $f = 100\text{MHz}$	100	-	-	MHz

Typical Characteristics : $T_A = 25^\circ\text{C}$ unless otherwise specified


Ratings & Characteristic Curves



$V_{CE} = 5\text{ V}$

- (1) $T_{amb} = 150^\circ\text{C}$
- (2) $T_{amb} = 25^\circ\text{C}$
- (3) $T_{amb} = -55^\circ\text{C}$

Selection A : DC current gain as a function of collector current; typical values




$V_{CE} = 5\text{ V}$

- (1) $T_{amb} = -55^\circ\text{C}$
- (2) $T_{amb} = 25^\circ\text{C}$
- (3) $T_{amb} = 150^\circ\text{C}$

Selection A : Base-emitter voltage as a function of collector current; typical values


NPN Transistor



$I_C/I_B = 20$

- (1) $T_{amb} = 150\text{ }^\circ\text{C}$
- (2) $T_{amb} = 25\text{ }^\circ\text{C}$
- (3) $T_{amb} = -55\text{ }^\circ\text{C}$

Selection A : Collector-emitter saturation voltage as a function of collector current; typical values




$I_C/I_B = 10$

- (1) $T_{amb} = -55\text{ }^\circ\text{C}$
- (2) $T_{amb} = 25\text{ }^\circ\text{C}$
- (3) $T_{amb} = 150\text{ }^\circ\text{C}$

Selection A : Base-emitter saturation voltage as a function of collector current; typical values

Package Outline


Plastic surface mounted package



Dimensions : Millimetres

Package outline SOT23

Soldering Footprint



- solder lands
- solder resist
- solder paste
- occupied area

Dimensions : Millimetres

Reflow soldering footprint SOT23

Package Information :

Device	Package	Shipping
BC846 BC846A BC846B	SOT-23	3,000 / Tape & Reel

Part Number Table

Description	Part Number	Identifier
Transistor, NPN, 0.1A, 65V, SOT23	BC846	1B
	BC846A	1A
	BC846B	part number + 1B

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.