
## KEMET Part Number: FA1A223ZF

(USCFA01A223Z00)



Padial Cylindrical Double Laver

## Supercapacitors, Radial Pin, Commercial Grade, FA, 0.022 F, -20/+80%, 11 V, Pin Leads, Lead Spacing = 5.1mm



| Description:   | Capacitor                |  |
|----------------|--------------------------|--|
| RoHS:          | Yes                      |  |
| Miscellaneous: | DischargeValue = 0.035 F |  |
|                |                          |  |
|                |                          |  |
| Specifications |                          |  |

**General Information** 

FA

Series:

| Dimensions  |                |  |
|-------------|----------------|--|
| D           | 16mm +/-0.5mm  |  |
| L           | 25mm MAX       |  |
| S           | 5.1mm +/-0.5mm |  |
| LL Negative | 7mm MIN        |  |
| LL Positive | 5mm MIN        |  |

| Packaging Specifications |           |
|--------------------------|-----------|
| Lead:                    | Pin Leads |
| Packaging:               | Bulk      |

| Specifications         |                    |
|------------------------|--------------------|
| Capacitance:           | 0.022 F            |
| Capacitance Tolerance: | -20/+80%           |
| Voltage DC:            | 11 VDC             |
| Temperature Range:     | -25/+70C           |
| Rated Temperature:     | 70C                |
| Resistance:            | 20000 mOhms (1kHz) |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

