

## SAFETY DATA SHEET

### Polyurethane Resin UR5048, Part A

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

#### 1. Identification

##### Product identifier

**Product name** Polyurethane Resin UR5048, Part A

**Product number** UR5048A, EUR5048RP250G, EUR5048RP250GE, EUR5048RP350G, EUR5048RP500G, EUR5048RP600G, EUR5048K1K, EUR5048K5K, ZE

##### Recommended use of the chemical and restrictions on use

**Application** Resin.

**Uses advised against** No specific uses advised against are identified.

##### Details of the supplier of the safety data sheet

##### Supplier

ELECTROLUBE. A division of HK WENTWORTH LTD  
HK WENTWORTH-AMERICA  
PO Box 126257  
Benbrook, Texas 76126  
USA  
info@hkw.us.com  
+1 888-501-9203

##### Emergency telephone number

**Emergency telephone** +1 202 464 2554 (USA only)  
+44 1235 239670

#### 2. Hazard(s) identification

##### Classification of the substance or mixture

**Physical hazards** Not Classified

**Health hazards** Not Classified

**Environmental hazards** Not Classified

##### Label elements

**Hazard statements** NC Not Classified

##### Other hazards

This product does not contain any substances classified as PBT or vPvB.

#### 3. Composition/information on ingredients

##### Mixtures

**Composition comments** None of the ingredients are required to be listed.

#### 4. First-aid measures

##### Description of first aid measures

## Polyurethane Resin UR5048, Part A

<b>General information</b>	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
<b>Skin Contact</b>	Remove affected person from source of contamination. Rinse immediately with plenty of water.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue.

### Most important symptoms and effects, both acute and delayed

<b>General information</b>	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	Prolonged inhalation of high concentrations may damage respiratory system.
<b>Ingestion</b>	Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.
<b>Skin contact</b>	Prolonged contact may cause dryness of the skin.
<b>Eye contact</b>	May cause temporary eye irritation.

### Indication of immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Treat symptomatically.
<b>Specific treatments</b>	No special treatment required.

## 5. Fire-fighting measures

### Extinguishing media

<b>Suitable extinguishing media</b>	The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

### Special hazards arising from the substance or mixture

<b>Specific hazards</b>	Containers can burst violently or explode when heated, due to excessive pressure build-up.
<b>Hazardous combustion products</b>	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

### Advice for firefighters

<b>Protective actions during firefighting</b>	Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
---	---

## Polyurethane Resin UR5048, Part A

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

**Personal precautions** No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage.

#### Environmental precautions

**Environmental precautions** Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

#### Methods and material for containment and cleaning up

**Methods for cleaning up** Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Reuse or recycle products wherever possible. Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labeled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**Reference to other sections** For personal protection, see Section 8.

### 7. Handling and storage

#### Precautions for safe handling

**Usage precautions** Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists.

**Advice on general occupational hygiene** Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

#### Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in accordance with local regulations.

**Storage class** Chemical storage.

#### Specific end uses(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.

### 8. Exposure Controls/personal protection

#### Control parameters

#### Occupational exposure limits

## Polyurethane Resin UR5048, Part A

### xylene

Long-term exposure limit (8-hour TWA): OSHA 100 ppm 435 mg/m<sup>3</sup>

Long-term exposure limit (8-hour TWA): ACGIH 100 ppm 434 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): ACGIH 150 ppm 651 mg/m<sup>3</sup>

A4

OSHA = Occupational Safety and Health Administration.

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

### Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Provide adequate ventilation. Good general ventilation should be adequate to control worker exposure to airborne contaminants.

#### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with OSHA 1910.133. The following protection should be worn: Chemical splash goggles.

#### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

#### Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

#### Hygiene measures

Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke.

#### Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Provide adequate ventilation. Large Spillages: If ventilation is inadequate, suitable respiratory protection must be worn.

#### Environmental exposure controls

Not regarded as dangerous for the environment.

## 9. Physical and Chemical Properties

### Information on basic physical and chemical properties

Appearance	Liquid.
Color	Clear.
Odor	Characteristic.
pH	Not available.
Melting point	Not available.

## Polyurethane Resin UR5048, Part A

<b>Initial boiling point and range</b>	Not available.
<b>Flash point</b>	Not available.
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	Not available.
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	Not available.
<b>Bulk density</b>	0.93 kg/l
<b>Solubility(ies)</b>	Not available.
<b>Partition coefficient</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	60 mPa s @ 23°C/73.4°F
<b>Explosive properties</b>	Not considered to be explosive.
<b>Oxidizing properties</b>	Does not meet the criteria for classification as oxidizing.

### 10. Stability and reactivity

<b>Reactivity</b>	There are no known reactivity hazards associated with this product.
<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
<b>Possibility of hazardous reactions</b>	No potentially hazardous reactions known.
<b>Conditions to avoid</b>	There are no known conditions that are likely to result in a hazardous situation.
<b>Materials to avoid</b>	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
<b>Hazardous decomposition products</b>	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

### 11. Toxicological information

#### Information on toxicological effects

<b>Toxicological effects</b>	Not regarded as a health hazard under current legislation.
<b><u>Acute toxicity - oral</u></b>	
<b>Notes (oral LD<sub>50</sub>)</b>	Based on available data the classification criteria are not met.
<b>ATE oral (mg/kg)</b>	3,531.07
<b><u>Acute toxicity - dermal</u></b>	
<b>Notes (dermal LD<sub>50</sub>)</b>	Based on available data the classification criteria are not met.
<b>ATE dermal (mg/kg)</b>	3,531.07

## Polyurethane Resin UR5048, Part A

### Acute toxicity - inhalation

**Notes (inhalation LC<sub>50</sub>)** Based on available data the classification criteria are not met.

**ATE inhalation (gases ppm)** 70,621.47

**ATE inhalation (vapours mg/l)** 353.11

**ATE inhalation (dusts/mists mg/l)** 35.31

### Skin corrosion/irritation

**Animal data** Based on available data the classification criteria are not met.

### Serious eye damage/irritation

**Serious eye damage/irritation** Based on available data the classification criteria are not met.

### Respiratory sensitization

**Respiratory sensitization** Based on available data the classification criteria are not met.

### Skin sensitization

**Skin sensitization** Based on available data the classification criteria are not met.

### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

### **IARC carcinogenicity**

Contains a substance which may be potentially carcinogenic. IARC Group 3 Not classifiable as to its carcinogenicity to humans.

### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

**Reproductive toxicity - development** Based on available data the classification criteria are not met.

### Specific target organ toxicity - single exposure

**STOT - single exposure** Not classified as a specific target organ toxicant after a single exposure.

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Not classified as a specific target organ toxicant after repeated exposure.

### Aspiration hazard

**Aspiration hazard** Based on available data the classification criteria are not met.

### **General information**

No specific health hazards known. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

### **Inhalation**

Prolonged inhalation of high concentrations may damage respiratory system.

### **Ingestion**

Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.

### **Skin Contact**

Prolonged contact may cause dryness of the skin.

### **Eye contact**

May cause temporary eye irritation.

### **Route of entry**

Ingestion Inhalation Skin and/or eye contact

### **Target Organs**

No specific target organs known.

## Polyurethane Resin UR5048, Part A

### xylene

#### Acute toxicity - dermal

ATE dermal (mg/kg) 1,100.0

#### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 27.571

Species Mouse

ATE inhalation (vapours mg/l) 27.571

#### Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

### 12. Ecological Information

**Ecotoxicity** Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

**Toxicity** Based on available data the classification criteria are not met.

#### Persistence and degradability

**Persistence and degradability** The degradability of the product is not known.

#### Bioaccumulative potential

**Bio-Accumulative Potential** No data available on bioaccumulation.

**Partition coefficient** Not available.

#### Mobility in soil

**Mobility** No data available.

#### Other adverse effects

**Other adverse effects** None known.

### 13. Disposal considerations

#### Waste treatment methods

**General information** The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.

**Disposal methods** Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of the local water authority.

### 14. Transport information

**General** The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT).

## Polyurethane Resin UR5048, Part A

**UN Number**

Not applicable.

**UN proper shipping name**

Not applicable.

**Transport hazard class(es)**

No transport warning sign required.

**DOT transport labels**

No transport warning sign required.

**Packing group**

Not applicable.

**Environmental hazards****Environmentally Hazardous Substance**

No.

**Special precautions for user**

Not applicable.

**DOT TIH Zone**

Not applicable.

Transport in bulk according to Not applicable.

**Annex II of MARPOL 73/78  
and the IBC Code****15. Regulatory information****US Federal Regulations****SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities**

None of the ingredients are listed or exempt.

**CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)**

The following ingredients are listed or exempt:

*xylene*

Final CERCLA RQ: 100(45.4) pounds (Kilograms)

**SARA Extremely Hazardous Substances EPCRA Reportable Quantities**

None of the ingredients are listed or exempt.

**SARA 313 Emission Reporting**

The following ingredients are listed or exempt:

*xylene*

1.0 %

0.1 %

*(neodecanoato-O)phenylmercury*

0 %

**CAA Accidental Release Prevention**

None of the ingredients are listed or exempt.

**FDA - Essential Chemical**

None of the ingredients are listed or exempt.



## Polyurethane Resin UR5048, Part A

### FDA - Precursor Chemical

None of the ingredients are listed or exempt.

### SARA (311/312) Hazard Categories

None of the ingredients are listed or exempt.

### OSHA Highly Hazardous Chemicals

None of the ingredients are listed or exempt.

### US State Regulations

#### California Proposition 65 Carcinogens and Reproductive Toxins

The following ingredients are listed or exempt:

*1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich*

Known to the State of California to cause developmental and reproductive toxicity.

#### California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed or exempt:

*xylene*

Present.

#### California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

#### California Directors List of Hazardous Substances

The following ingredients are listed or exempt:

*xylene*

Present.

#### Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

*xylene*

Present.

#### Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

*xylene*

Present.

#### Minnesota "Right To Know" List

The following ingredients are listed or exempt:

*xylene*

Present.

#### New Jersey "Right To Know" List

The following ingredients are listed or exempt:

*xylene*

Present.

#### Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

*xylene*

Present.

### Inventories

## Polyurethane Resin UR5048, Part A

### US - TSCA

All the ingredients are listed or exempt.

### US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

### 16. Other information

<b>Training advice</b>	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
<b>Issued by</b>	Bethan Massey
<b>Revision date</b>	10/30/2016
<b>Revision</b>	0
<b>SDS No.</b>	568

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

## SAFETY DATA SHEET

### Polyurethane Resin UR5048, Part B

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

#### 1. Identification

##### Product identifier

**Product name** Polyurethane Resin UR5048, Part B

**Product number** UR5048B, EUR5048RP250G, EUR5048RP250GE, EUR5048RP350G, EUR5048RP500G, EUR5048RP600G, EUR5048K1K, EUR5048K5K, ZE

##### Recommended use of the chemical and restrictions on use

**Application** Hardener.

**Uses advised against** No specific uses advised against are identified.

##### Details of the supplier of the safety data sheet

##### Supplier

ELECTROLUBE. A division of HK WENTWORTH LTD  
 HK WENTWORTH-AMERICA  
 PO Box 126257  
 Benbrook, Texas 76126  
 USA  
 info@hkw.us.com  
 +1 888-501-9203

##### Emergency telephone number

**Emergency telephone** +1 202 464 2554 (USA only)  
 +44 1235 239670

#### 2. Hazard(s) identification

##### Classification of the substance or mixture


**Physical hazards** Not Classified

**Health hazards** Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Resp. Sens. 1 - H334 Skin Sens. 1 - H317 Carc. 2 - H351 STOT SE 3 - H335 STOT RE 2 - H373

**Environmental hazards** Not Classified

##### Label elements

##### Pictogram



##### Signal word

Danger

## Polyurethane Resin UR5048, Part B

### Hazard statements

H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 H335 May cause respiratory irritation.  
 H351 Suspected of causing cancer.  
 H373 May cause damage to organs through prolonged or repeated exposure.

### Precautionary statements

P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P260 Do not breathe vapor/ spray.  
 P261 Avoid breathing vapor/ spray.  
 P264 Wash contaminated skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P272 Contaminated work clothing must not be allowed out of the workplace.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
 P284 [In case of inadequate ventilation] wear respiratory protection.  
 P302+P352 If on skin: Wash with plenty of water.  
 P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308+P313 If exposed or concerned: Get medical advice/ attention.  
 P312 Call a poison center/ doctor if you feel unwell.  
 P314 Get medical advice/ attention if you feel unwell.  
 P321 Specific treatment (see medical advice on this label).  
 P332+P313 If skin irritation occurs: Get medical advice/ attention.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.  
 P337+P313 If eye irritation persists: Get medical advice/ attention.  
 P342+P311 If experiencing respiratory symptoms: Call a poison center/ doctor.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.  
 P501 Dispose of contents/ container in accordance with national regulations.

### Contains

methylenediphenyl diisocyanate , Diphenylmethane-4,4-Diisocyanate (MDI) Isomers

### Other hazards

This product does not contain any substances classified as PBT or vPvB.

### 3. Composition/information on ingredients

#### Mixtures

## Polyurethane Resin UR5048, Part B

<b>methylenediphenyl diisocyanate</b>	<b>60-100%</b>
CAS number: 26447-40-5	
<b>Classification</b>	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Irrit. 2A - H319	
Resp. Sens. 1 - H334	
Skin Sens. 1 - H317	
Carc. 2 - H351	
STOT SE 3 - H335	
STOT RE 2 - H373	
<b>Diphenylmethane-4,4-Diisocyanate (MDI) Isomers</b>	<b>30-60%</b>
CAS number: 9016-87-9	
<b>Classification</b>	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Irrit. 2A - H319	
Resp. Sens. 1 - H334	
Skin Sens. 1 - H317	
Carc. 2 - H351	
STOT SE 3 - H335	
STOT RE 2 - H373	

The full text for all hazard statements is displayed in Section 16.

### 4. First-aid measures

#### Description of first aid measures

<b>General information</b>	Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
<b>Inhalation</b>	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place. In the event of any sensitization symptoms developing, ensure further exposure is avoided.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
<b>Skin Contact</b>	It is important to remove the substance from the skin immediately. In the event of any sensitization symptoms developing, ensure further exposure is avoided. Remove contamination with soap and water or recognized skin cleansing agent. Get medical attention if symptoms are severe or persist after washing.

## Polyurethane Resin UR5048, Part B

<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue. If it is suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.
<b><u>Most important symptoms and effects, both acute and delayed</u></b>	
<b>General information</b>	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	May cause sensitization or allergic reactions in sensitive individuals. A single exposure may cause the following adverse effects: Headache. Exhaustion and weakness. Prolonged or repeated exposure may cause the following adverse effects: Suspected of causing cancer.
<b>Ingestion</b>	May cause sensitization or allergic reactions in sensitive individuals. May cause irritation. Prolonged or repeated exposure may cause the following adverse effects: Suspected of causing cancer.
<b>Skin contact</b>	May cause skin sensitization or allergic reactions in sensitive individuals. Redness. Irritating to skin. Prolonged or repeated exposure may cause the following adverse effects: Suspected of causing cancer.
<b>Eye contact</b>	Irritating to eyes.

### **Indication of immediate medical attention and special treatment needed**

**Notes for the doctor**                      Treat symptomatically. May cause sensitization or allergic reactions in sensitive individuals.

### **5. Fire-fighting measures**

#### **Extinguishing media**

**Suitable extinguishing media**      The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

**Unsuitable extinguishing media**      Do not use water jet as an extinguisher, as this will spread the fire.

#### **Special hazards arising from the substance or mixture**

**Specific hazards**                              Containers can burst violently or explode when heated, due to excessive pressure build-up. This product is toxic.

**Hazardous combustion products**      Thermal decomposition or combustion products may include the following substances: Toxic gases or vapors.

#### **Advice for firefighters**

**Protective actions during firefighting**      Avoid breathing fire gases or vapors. Evacuate area. Keep upwind to avoid inhalation of gases, vapors, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

**Special protective equipment for firefighters**      Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

## Polyurethane Resin UR5048, Part B

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

##### **Personal precautions**

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Avoid inhalation of vapors and spray/mists. Use suitable respiratory protection if ventilation is inadequate. Avoid contact with skin and eyes.

#### Environmental precautions

##### **Environmental precautions**

Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

#### Methods and material for containment and cleaning up

##### **Methods for cleaning up**

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Provide adequate ventilation. Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labeled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

##### **Reference to other sections**

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

### 7. Handling and storage

#### Precautions for safe handling

##### **Usage precautions**

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Suspected of causing cancer. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

##### **Advice on general occupational hygiene**

Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

#### Conditions for safe storage, including any incompatibilities

##### **Storage precautions**

Store away from incompatible materials (see Section 10). Store in accordance with local regulations. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Utilize retaining walls to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

## Polyurethane Resin UR5048, Part B

**Storage class** Chemical storage.

**Specific end uses(s)**

**Specific end use(s)** The identified uses for this product are detailed in Section 1.

### 8. Exposure Controls/personal protection

#### Exposure controls

##### Protective equipment



##### Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimize worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimize exposure.

##### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with OSHA 1910.133. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

##### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

##### Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

##### Hygiene measures

Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.

##### Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with OSHA 1910.134. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134.

##### Environmental exposure controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.



## Polyurethane Resin UR5048, Part B

### 9. Physical and Chemical Properties

#### Information on basic physical and chemical properties

<b>Appearance</b>	Liquid.
<b>Color</b>	Clear.
<b>Odor</b>	No characteristic odor.
<b>pH</b>	Not available.
<b>Melting point</b>	Not available.
<b>Initial boiling point and range</b>	Not available.
<b>Flash point</b>	Not available.
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	Not available.
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	Not available.
<b>Bulk density</b>	1.24 kg/l
<b>Solubility(ies)</b>	Not available.
<b>Partition coefficient</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	60 mPa s @ 23°C/73.4°F
<b>Explosive properties</b>	Not considered to be explosive.
<b>Oxidizing properties</b>	Does not meet the criteria for classification as oxidizing.

### 10. Stability and reactivity

<b>Reactivity</b>	See the other subsections of this section for further details.
<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
<b>Possibility of hazardous reactions</b>	No potentially hazardous reactions known.
<b>Conditions to avoid</b>	There are no known conditions that are likely to result in a hazardous situation.
<b>Materials to avoid</b>	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
<b>Hazardous decomposition products</b>	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic gases or vapors.

### 11. Toxicological information

#### Information on toxicological effects

## Polyurethane Resin UR5048, Part B

### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** Based on available data the classification criteria are not met.

### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** Based on available data the classification criteria are not met.

### Acute toxicity - inhalation

**Notes (inhalation LC<sub>50</sub>)** Acute Tox. 4 - H332 Harmful if inhaled.

**ATE inhalation (gases ppm)** 15,000.0

**ATE inhalation (vapours mg/l)** 36.67

**ATE inhalation (dusts/mists mg/l)** 1.5

### Skin corrosion/irritation

**Animal data** Irritating.

### Serious eye damage/irritation

**Serious eye damage/irritation** Causes serious eye irritation.

### Respiratory sensitization

**Respiratory sensitization** There is evidence that the product can cause respiratory hypersensitivity.

### Skin sensitization

**Skin sensitization** May cause skin sensitization or allergic reactions in sensitive individuals.

### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

### Carcinogenicity

**Carcinogenicity** Suspected of causing cancer.

### IARC carcinogenicity

None of the ingredients are listed or exempt.

### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

**Reproductive toxicity - development** Based on available data the classification criteria are not met.

### Specific target organ toxicity - single exposure

**STOT - single exposure** STOT SE 3 - H335 May cause respiratory irritation.

**Target organs** Respiratory system, lungs

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** STOT RE 2 - H373 May cause damage to organs through prolonged or repeated exposure.

### Aspiration hazard

**Aspiration hazard** Based on available data the classification criteria are not met.

### **General information**

May cause cancer after repeated exposure. Risk of cancer depends on duration and level of exposure. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

### **Inhalation**

May cause sensitization or allergic reactions in sensitive individuals. A single exposure may cause the following adverse effects: Headache. Exhaustion and weakness.

## Polyurethane Resin UR5048, Part B

<b>Ingestion</b>	May cause sensitization or allergic reactions in sensitive individuals. May cause irritation.
<b>Skin Contact</b>	May cause skin sensitization or allergic reactions in sensitive individuals. Redness. Irritating to skin.
<b>Eye contact</b>	Irritating to eyes.
<b>Route of entry</b>	Ingestion Inhalation Skin and/or eye contact
<b>Target Organs</b>	Respiratory system, lungs
<b>Medical considerations</b>	Skin disorders and allergies.

### methylenediphenyl diisocyanate

#### Acute toxicity - inhalation

**ATE inhalation** 1.5  
(dusts/mists mg/l)

### Diphenylmethane-4,4-Diisocyanate (MDI) Isomers

#### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** Based on available data the classification criteria are not met.

#### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** Based on available data the classification criteria are not met.

#### Acute toxicity - inhalation

**Notes (inhalation LC<sub>50</sub>)** Acute Tox. 4 - H332 Harmful if inhaled.

**ATE inhalation (gases** 4,500.0  
**ppm)**

**ATE inhalation (vapours** 11.0  
**mg/l)**

**ATE inhalation** 1.5  
**(dusts/mists mg/l)**

#### Skin corrosion/irritation

**Animal data** Irritating.

#### Serious eye damage/irritation

**Serious eye** Causes serious eye irritation.  
**damage/irritation**

#### Respiratory sensitization

**Respiratory sensitization** There is evidence that the product can cause respiratory hypersensitivity.

#### Skin sensitization

**Skin sensitization** May cause skin sensitization or allergic reactions in sensitive individuals.

#### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

#### Carcinogenicity

**Carcinogenicity** Suspected of causing cancer.

**IARC carcinogenicity** None of the ingredients are listed or exempt.

## Polyurethane Resin UR5048, Part B

### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

**Reproductive toxicity - development** Based on available data the classification criteria are not met.

### Specific target organ toxicity - single exposure

**STOT - single exposure** STOT SE 3 - H335 May cause respiratory irritation.

**Target organs** Respiratory system, lungs

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** STOT RE 2 - H373 May cause damage to organs through prolonged or repeated exposure.

### Aspiration hazard

**Aspiration hazard** Based on available data the classification criteria are not met.

### **General information**

May cause cancer after repeated exposure. Risk of cancer depends on duration and level of exposure. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

### **Inhalation**

May cause sensitization or allergic reactions in sensitive individuals. A single exposure may cause the following adverse effects: Headache. Exhaustion and weakness.

### **Ingestion**

May cause sensitization or allergic reactions in sensitive individuals. May cause irritation.

### **Skin Contact**

May cause skin sensitization or allergic reactions in sensitive individuals. Redness. Irritating to skin.

### **Eye contact**

Irritating to eyes.

### **Route of entry**

Ingestion Inhalation Skin and/or eye contact

### **Target Organs**

Respiratory system, lungs

### **Medical considerations**

Skin disorders and allergies.

## 12. Ecological Information

### **Ecotoxicity**

Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

### Diphenylmethane-4,4-Diisocyanate (MDI) Isomers

### **Ecotoxicity**

Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

### **Toxicity**

Based on available data the classification criteria are not met.

### Diphenylmethane-4,4-Diisocyanate (MDI) Isomers

### **Toxicity**

Based on available data the classification criteria are not met.

## Polyurethane Resin UR5048, Part B

### Persistence and degradability

**Persistence and degradability** The degradability of the product is not known.

### Diphenylmethane-4,4-Diisocyanate (MDI) Isomers

**Persistence and degradability** The degradability of the product is not known.

### Bioaccumulative potential

**Bio-Accumulative Potential** No data available on bioaccumulation.

**Partition coefficient** Not available.

### Diphenylmethane-4,4-Diisocyanate (MDI) Isomers

**Bio-Accumulative Potential** No data available on bioaccumulation.

**Partition coefficient** Not available.

### Mobility in soil

**Mobility** No data available.

### Diphenylmethane-4,4-Diisocyanate (MDI) Isomers

**Mobility** No data available.

### Other adverse effects

**Other adverse effects** None known.

### Diphenylmethane-4,4-Diisocyanate (MDI) Isomers

**Other adverse effects** None known.

## 13. Disposal considerations

### Waste treatment methods

#### **General information**

The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

#### **Disposal methods**

Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

## 14. Transport information

### **General**

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT).

## Polyurethane Resin UR5048, Part B

**UN Number**

Not applicable.

**UN proper shipping name**

Not applicable.

**Transport hazard class(es)**

No transport warning sign required.

**DOT transport labels**

No transport warning sign required.

**Packing group**

Not applicable.

**Environmental hazards****Environmentally Hazardous Substance**

No.

**Special precautions for user**

Not applicable.

**DOT TIH Zone**

Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Annex II of MARPOL 73/78  
and the IBC Code

**15. Regulatory information****US Federal Regulations****SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities**

None of the ingredients are listed or exempt.

**CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)**

None of the ingredients are listed or exempt.

**SARA Extremely Hazardous Substances EPCRA Reportable Quantities**

None of the ingredients are listed or exempt.

**SARA 313 Emission Reporting**

None of the ingredients are listed or exempt.

**CAA Accidental Release Prevention**

None of the ingredients are listed or exempt.

**FDA - Essential Chemical**

None of the ingredients are listed or exempt.

**FDA - Precursor Chemical**

None of the ingredients are listed or exempt.

**SARA (311/312) Hazard Categories**

None of the ingredients are listed or exempt.

## Polyurethane Resin UR5048, Part B

### OSHA Highly Hazardous Chemicals

None of the ingredients are listed or exempt.

### US State Regulations

#### California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are listed or exempt.

#### California Air Toxics "Hot Spots" (A-I)

None of the ingredients are listed or exempt.

#### California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

#### California Directors List of Hazardous Substances

None of the ingredients are listed or exempt.

#### Massachusetts "Right To Know" List

None of the ingredients are listed or exempt.

#### Rhode Island "Right To Know" List

None of the ingredients are listed or exempt.

#### Minnesota "Right To Know" List

None of the ingredients are listed or exempt.

#### New Jersey "Right To Know" List

None of the ingredients are listed or exempt.

#### Pennsylvania "Right To Know" List

None of the ingredients are listed or exempt.

### Inventories

#### US - TSCA

The following ingredients are listed or exempt:

*methylenediphenyl diisocyanate*

#### US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

### 16. Other information

#### Classification abbreviations and acronyms

Acute Tox. = Acute toxicity  
 Carc. = Carcinogenicity  
 Eye Irrit. = Eye irritation  
 Resp. Sens. = Respiratory sensitisation  
 Skin Irrit. = Skin irritation  
 Skin Sens. = Skin sensitisation  
 STOT RE = Specific target organ toxicity-repeated exposure  
 STOT SE = Specific target organ toxicity-single exposure

#### Training advice

Read and follow manufacturer's recommendations. Only trained personnel should use this material.

#### Issued by

Bethan Massey

#### Revision date

11/15/2016

#### Revision

0

## Polyurethane Resin UR5048, Part B

**SDS No.** 571

**Hazard statements in full**

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.